

FIG. 1

$$\square rd_{128} = m[rc](128*64/size) * rb_{128}$$

$$m[rc](128*64/size)$$




FIG. 2




FIG. 3




FIG. 4

$$\square \text{ specifier} = \text{address} + (\text{size}/2) + (\text{width}/2)$$





FIG. 5




FIG. 6




FIG. 7






FIG. 8

☐ *wmc.c* contents



☐ *wmc.pa*—physical address



☐ *wmc.size*—size of contents



☐ *wmc.cv*—contents valid



☐ *wmc.th*—thread last used



☐ *wmc.reg*—register last used



☐ *wmc.rtv*—register & thread valid



FIG. 9




FIG. 10




FIG. 11




Fig. 12





Fig. 13



memory management organization

Fig. 14




Fig. 15

```

def data,flags ← AccessPhysicalLTB(pa,op,wdata) as
  th ← pa23..19
  en ← pa6..4
  if (en < (1 || 0LE)) and (th < T) and (pa18..6=0) then
    case op of
      R:
        data ← 064 || LTBArray[th][en]
      W:
        LocalTB[th][en] ← wdata63..0
    endcase
  else
    data ← 0
  endif
enddef

```

Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21

```

def ga,LocalProtect ← LocalTranslation(th,ba,la,pl) as
  if LB & (ba63..48 ⊕ la63..48) then
    raise AccessDisallowedByVirtualAddress
  endif
  me ← NONE
  for i ← 0 to (1 || 0LE)-1
    if (la63..48 & ~LocalTB[th][i]63..48) = LocalTB[th][i]47..32 then
      me ← i
    endif
  endfor
  if me = NONE then
    if ~ControlRegisterpl+8 then
      raise LocalTBMiss
    endif
    ga ← la
    LocalProtect ← 0
  else
    ga ← (va63..48 ^ LocalTB[th][me]31..16) || va47..0
    LocalProtect ← LocalTB[th][me]15..0
  endif
enddef

```

Fig. 22




Fig. 23

```

def data,flags ← AccessPhysicalGTB(pa,op,wdata) as
  th ← pa23..19+GT || 0GT
  en ← pa18..4
  if (en < (1 || 0G)) and (th < T) and (pa18+GT..19 = 0) then
    case op of
      R:
        data ← GTBArray[th5..GT][en]
      W:
        GTBArray[th5..GT][en] ← wdata
    endcase
  else
    data ← 0
  endif
enddef

```

Fig. 24




Fig. 25

```

def pa,GlobalProtect ← GlobalAddressTranslation(th,ga,pl,lda) as
  me ← NONE
  for i ← 0 to (1 || 0G) - 1
    if GlobalTB[th5..GT][i] ≠ 0 then
      size ← (GlobalTB[th5..GT][i]63..7 and (064-GlobalTB[th5..GT][i]63..7)) || 08
      if ((ga63..8 || 08) ^ (GlobalTB[th5..GT][i]63..8 || 08)) and (064-size) = 0 then
        me ← GlobalTB[th5..GT][i]
      endif
    endif
  endfor
  if me = NONE then
    if lda then
      PerformAccessDetail(AccessDetailRequiredByLocalTB)
    endif
    raise GlobalTBMiss
  else
    pa ← (ga63..8 ^ GlobalTB[th5..GT][me]127..72) || ga7..0
    GlobalProtect ← GlobalTB[th5..GT][me]71..64 || 01 || GlobalTB[th5..GT][me]6..0
  endif
enddef

```

Fig. 26

```

def GTBUpdateWrite(th,fill,data) as
  me ← NONE
  for i ← 0 to (1 || 0G) - 1
    size ← (GlobalTB[th5..GT][i]63..7 and (064-GlobalTB(th5..GT)[i]63..7)) || 08
    if ((data63..8||08) ^ (GlobalTB[th5..GT][i]63..8||08)) and (064-size) = 0 then
      me ← i
    endif
  endfor
  if me = NONE then
    if fill then
      GlobalTB[th5..GT][GTBLast[th5..GT]] ← data
      GTBLast[th5..GT] ← (GTBLast[th5..GT] + 1)G-1..0
      if GTBLast[th5..GT] = 0 then
        GTBLast[th5..GT] ← GTBFirst[th5..GT]
        GTBBump[th5..GT] ← 1
      endif
    endif
  else
    GlobalTB[th5..GT][me] ← data
  endif
enddef

```

Fig. 27




Fig. 28




Fig. 29


```

def data,flags ← AccessPhysicalGTBRegisters(pa,op,wdata) as
  th ← pa23..19+GT || 0GT
  rn ← pa18..8
  if (rn < 5) and (th < T) and (pa18+GT..19 = 0) and (pa7..4 = 0) then
    case rn || op of
      0 || R, 1 || R:
        data ← 0
      0 || W, 1 || W:
        GTBUpdateWrite(th,rn0,wdata)
      2 || R:
        data ← 064-G || GTBLast[th5..GT]
      2 || W:
        GTBLast[th5..GT] ← wdataG-1..0
      3 || R:
        data ← 064-G || GTBFirst[th5..GT]
      3 || W:
        GTBFirst[th5..GT] ← wdataG-1..0
      3 || R:
        data ← 063 || GTBBump[th5..GT]
      3 || W:
        GTBBump[th5..GT] ← wdata0
    endcase
  else
    data ← 0
  endif
enddef

```

Fig. 30

| | |
|-----------|---------------|
| G.BOOLEAN | Group Boolean |
|-----------|---------------|

Equivalencies

| | |
|----------------|--|
| G.AAA | Group three-way and |
| G.AAA.1 | Group add add add bits |
| G.AAS.1 | Group add add subtract bits |
| G.ADD.1 | Group add bits |
| G.AND | Group and |
| G.ANDN | Group and not |
| G.COPY | Group copy |
| G.NAAA | Group three-way nand |
| G.NAND | Group nand |
| G.NOOO | Group three-way nor |
| G.NOR | Group nor |
| G.NOT | Group not |
| G.NXXX | Group three-way exclusive-nor |
| G.OOO | Group three-way or |
| G.OR | Group or |
| G.ORN | Group or not |
| G.SAA.1 | Group subtract add add bits |
| G.SAS.1 | Group subtract add subtract bits |
| G.SET | Group set |
| G.SET.AND.E.1 | Group set and equal zero bits |
| G.SET.AND.NE.1 | Group set and not equal zero bits |
| G.SET.E.1 | Group set equal bits |
| G.SET.G.1 | Group set greater signed bits |
| G.SET.G.U.1 | Group set greater unsigned bits |
| G.SET.G.Z.1 | Group set greater zero signed bits |
| G.SET.GE.1 | Group set greater equal signed bits |
| G.SET.GE.Z.1 | Group set greater equal zero signed bits |
| G.SET.L.1 | Group set less signed bits |
| G.SET.L.Z.1 | Group set less zero signed bits |
| G.SET.LE.1 | Group set less equal signed bits |
| G.SET.LE.U.1 | Group set less equal unsigned bits |
| G.SET.LE.Z.1 | Group set less equal zero signed bits |
| G.SET.NE.1 | Group set not equal bits |
| G.SET.GE.U.1 | Group set greater equal unsigned bits |
| G.SET.L.U.1 | Group set less unsigned bits |

Fig. 31A

| | |
|---------|---------------------------------------|
| G.SSA.1 | Group subtract subtract add bits |
| G.SSS.1 | Group subtract subtract subtract bits |
| G.SUB.1 | Group subtract bits |
| G.XNOR | Group exclusive-nor |
| G.XOR | Group exclusive-or |
| G.XXX | Group three-way exclusive-or |
| G.ZERO | Group zero |

| | | |
|-------------------------|---|-------------------------------------|
| G.AAA rd@rc,rb | ← | G.BOOLEAN rd@rc,rb,0b10000000 |
| G.AAA.1 rd@rc,rb | → | G.XXX rd@rc,rb |
| G.AAS.1 rd@rc,rb | → | G.XXX rd@rc,rb |
| G.ADD.1 rd=rc,rb | → | G.XOR rd=rc,rb |
| G.AND rd=rc,rb | ← | G.BOOLEAN rd@rc,rb,0b10001000 |
| G.ANDN rd=rc,rb | ← | G.BOOLEAN rd@rc,rb,0b01000100 |
| G.BOOLEAN rd@rb,rc,i | → | G.BOOLEAN rd@rc,rb,i7i5i6i4i3i1i2i0 |
| G.COPY rd=rc | ← | G.BOOLEAN rd@rc,rc,0b10001000 |
| G.NAAA. rd@rc,rb | ← | G.BOOLEAN rd@rc,rb,0b01111111 |
| G.NAND rd=rc,rb | ← | G.BOOLEAN rd@rc,rb,0b01110111 |
| G.NOOO rd@rc,rb | ← | G.BOOLEAN rd@rc,rb,0b00000001 |
| G.NOR rd=rc,rb | ← | G.BOOLEAN rd@rc,rb,0b00010001 |
| G.NOT rd=rc | ← | G.BOOLEAN rd@rc,rc,0b00010001 |
| G.NXXX rd@rc,rb | ← | G.BOOLEAN rd@rc,rb,0b01101001 |
| G.OOO rd@rc,rb | ← | G.BOOLEAN rd@rc,rb,0b11111110 |
| G.OR rd=rc,rb | ← | G.BOOLEAN rd@rc,rb,0b11101110 |
| G.ORN rd=rc,rb | ← | G.BOOLEAN rd@rc,rb,0b11011101 |
| G.SAA.1 rd@rc,rb | → | G.XXX rd@rc,rb |
| G.SAS.1 rd@rc,rb | → | G.XXX rd@rc,rb |
| G.SET rd | ← | G.BOOLEAN rd@rd,rd,0b10000001 |
| G.SET.AND.E.1 rd=rb,rc | → | G.NAND rd=rc,rb |
| G.SET.AND.NE.1 rd=rb,rc | → | G.AND rd=rc,rb |
| G.SET.E.1 rd=rb,rc | → | G.XNOR rd=rc,rb |
| G.SET.G.1 rd=rb,rc | → | G.ANDN rd=rc,rb |
| G.SET.G.U.1 rd=rb,rc | → | G.ANDN rd=rb,rc |
| G.SET.G.Z.1 rd=rc | → | G.ZERO rd |
| G.SET.GE.1 rd=rb,rc | → | G.ORN rd=rc,rb |
| G.SET.GE.Z.1 rd=rc | → | G.NOT rd=rc |

Fig. 31A (cont'd)

| | | |
|------------------------------|---|--------------------------------------|
| <i>G.SET.L.1 rd=rb,rc</i> | → | <i>G.ANDN rd=rb,rc</i> |
| <i>G.SET.L.Z.1 rd=rc</i> | → | <i>G.COPY rd=rc</i> |
| <i>G.SET.LE.1 rd=rb,rc</i> | → | <i>G.ORN rd=rb,rc</i> |
| <i>G.SET.LE.U.1 rd=rb,rc</i> | → | <i>G.ORN rd=rc,rb</i> |
| <i>G.SET.LE.Z.1 rd=rc</i> | → | <i>G.SET rd</i> |
| <i>G.SET.NE.1 rd=rb,rc</i> | → | <i>G.XOR rd=rc,rb</i> |
| <i>G.SET.GE.U.1 rd=rb,rc</i> | → | <i>G.ORN rd=rb,rc</i> |
| <i>G.SET.L.U.1 rd=rb,rc</i> | → | <i>G.ANDN rd=rc,rb</i> |
| <i>G.SSA.1 rd@rc,rb</i> | → | <i>G.XXX rd@rc,rb</i> |
| <i>G.SSS.1 rd@rc,rb</i> | → | <i>G.XXX rd@rc,rb</i> |
| <i>G.SUB.1 rd=rc,rb</i> | → | <i>G.XOR rd=rc,rb</i> |
| <i>G.XNOR rd=rc,rb</i> | ← | <i>G.BOOLEAN rd@rc,rb,0b10011001</i> |
| <i>G.XOR rd=rc,rb</i> | ← | <i>G.BOOLEAN rd@rc,rb,0b01100110</i> |
| <i>G.XXX rd@rc,rb</i> | ← | <i>G.BOOLEAN rd@rc,rb,0b10010110</i> |
| <i>G.ZERO rd</i> | ← | <i>G.BOOLEAN rd@rd,rd,0b00000000</i> |

Selection


| operation | function (binary) | function (decimal) |
|-----------|-------------------|--------------------|
| d | 11110000 | 240 |
| c | 11001100 | 204 |
| b | 10101010 | 176 |
| d&c&b | 10000000 | 128 |
| (d&c) b | 11101010 | 234 |
| d c b | 11111110 | 254 |
| d?c:b | 11001010 | 202 |
| d^c^b | 10010110 | 150 |
| ~d^c^b | 01101001 | 105 |
| 0 | 00000000 | 0 |

Fig. 31A (cont'd)

Format

G.BOOLEANrd@trc,trb,f

rd=gbooleani(rd,rc,rb,f)



```

if f6=f5 then
  if f2=f1 then
    if f2 then
      rc ← max(trc,trb)
      rb ← min(trc,trb)
    else
      rc ← min(trc,trb)
      rb ← max(trc,trb)
    endif
    ih ← 0
    il ← 0 || f6 || f7 || f4 || f3 || f0
  else
    if f2 then
      rc ← trb
      rb ← trc
    else
      rc ← trc
      rb ← trb
    endif
    ih ← 0
    il ← 1 || f6 || f7 || f4 || f3 || f0
  endif
else
  ih ← 1
  if f6 then
    rc ← trb
    rb ← trc
    il ← f1 || f2 || f7 || f4 || f3 || f0
  else
    rc ← trc
    rb ← trb
    il ← f2 || f1 || f7 || f4 || f3 || f0
  endif
endif

```

Fig. 31B

Definition

```
def GroupBoolean (ih,rd,rc,rb,il)
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  if ih=0 then
    if il5=0 then
      f ← il3 || il4 || il4 || il2 || il1 || (rc>rb)2 || il0
    else
      f ← il3 || il4 || il4 || il2 || il1 || 0 || 1 || il0
    endif
  else
    f ← il3 || 0 || 1 || il2 || il1 || il5 || il4 || il0
  endif
  for i ← 0 to 127 by size
    ai ← f(di||ci||bi)
  endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

none

Fig. 31C

Operation codes

| | |
|-------|-----------------|
| G.MUX | Group multiplex |
|-------|-----------------|

Redundancies

| | | |
|-------------------|---|-------------------------------|
| G.MUX ra=rd,rc,rc | ⇔ | G.COPY ra=rc |
| G.MUX ra=ra,rc,rb | ⇔ | G.BOOLEAN ra@rc,rb,0x11001010 |
| G.MUX ra=rd,ra,rb | ⇔ | G.BOOLEAN ra@rd,rb,0x11100010 |
| G.MUX ra=rd,rc,ra | ⇔ | G.BOOLEAN ra@rd,rc,0x11011000 |
| G.MUX ra=rd,rd,rb | ⇔ | G.OR ra=rd,rb |
| G.MUX ra=rd,rc,rd | ⇔ | G.AND ra=rd,rc |

Format

G.MUX ra=rd,rc,rb

ra=gmux(rd,rc,rb)




Fig. 31D

D finition

```
def GroupTernary(op,size,rd,rc,rb,ra) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  case op of
    G.MUX:
      a ← (c and d) or (b and not d)
  endcase
  RegWrite(ra, 128, a)
enddef
```

Exceptions

none

Fig. 31D

| | |
|---------------|--|
| G.ADD.8 | Group add bytes |
| G.ADD.16 | Group add doublets |
| G.ADD.32 | Group add quadlets |
| G.ADD.64 | Group add octlets |
| G.ADD.128 | Group add hexlet |
| G.ADD.L.8 | Group add limit signed bytes |
| G.ADD.L.16 | Group add limit signed doublets |
| G.ADD.L.32 | Group add limit signed quadlets |
| G.ADD.L.64 | Group add limit signed octlets |
| G.ADD.L.128 | Group add limit signed hexlet |
| G.ADD.L.U.8 | Group add limit unsigned bytes |
| G.ADD.L.U.16 | Group add limit unsigned doublets |
| G.ADD.L.U.32 | Group add limit unsigned quadlets |
| G.ADD.L.U.64 | Group add limit unsigned octlets |
| G.ADD.L.U.128 | Group add limit unsigned hexlet |
| G.ADD.8.O | Group add signed bytes check overflow |
| G.ADD.16.O | Group add signed doublets check overflow |
| G.ADD.32.O | Group add signed quadlets check overflow |
| G.ADD.64.O | Group add signed octlets check overflow |
| G.ADD.128.O | Group add signed hexlet check overflow |
| G.ADD.U.8.O | Group add unsigned bytes check overflow |
| G.ADD.U.16.O | Group add unsigned doublets check overflow |
| G.ADD.U.32.O | Group add unsigned quadlets check overflow |
| G.ADD.U.64.O | Group add unsigned octlets check overflow |
| G.ADD.U.128.O | Group add unsigned hexlet check overflow |

Fig. 32A

Format

G.op.size rd=rc,rb

rd=gopsize(rc,rb)




Fig. 32B

Definition

```
def Group(op,size,rd,rc,rb)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  case op of
    G.ADD:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow c_{i+size-1..i} + b_{i+size-1..i}$ 
      endfor
    G.ADD.L:
      for i ← 0 to 128-size by size
         $t \leftarrow (c_{i+size-1} \parallel c_{i+size-1..i}) + (b_{i+size-1} \parallel b_{i+size-1..i})$ 
         $a_{i+size-1..i} \leftarrow (t_{size} \neq t_{size-1}) ? (t_{size} \parallel t_{size-1}^{size-1}) : t_{size-1..0}$ 
      endfor
    G.ADD.L.U:
      for i ← 0 to 128-size by size
         $t \leftarrow (0^1 \parallel c_{i+size-1..i}) + (0^1 \parallel b_{i+size-1..i})$ 
         $a_{i+size-1..i} \leftarrow (t_{size} \neq 0) ? (1^{size}) : t_{size-1..0}$ 
      endfor
    G.ADD.O:
      for i ← 0 to 128-size by size
         $t \leftarrow (c_{i+size-1} \parallel c_{i+size-1..i}) + (b_{i+size-1} \parallel b_{i+size-1..i})$ 
        if  $t_{size} \neq t_{size-1}$  then
          raise FixedPointArithmetic
        endif
         $a_{i+size-1..i} \leftarrow t_{size-1..0}$ 
      endfor
    G.ADD.U.O:
      for i ← 0 to 128-size by size
         $t \leftarrow (0^1 \parallel c_{i+size-1..i}) + (0^1 \parallel b_{i+size-1..i})$ 
        if  $t_{size} \neq 0$  then
          raise FixedPointArithmetic
        endif
         $a_{i+size-1..i} \leftarrow t_{size-1..0}$ 
      endfor
  endcase
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Fixed-point arithmetic

Fig. 32C

Operation codes

| | |
|------------------|---|
| G.SET.AND.E.8 | Group set and equal zero bytes |
| G.SET.AND.E.16 | Group set and equal zero doublets |
| G.SET.AND.E.32 | Group set and equal zero quadlets |
| G.SET.AND.E.64 | Group set and equal zero octlets |
| G.SET.AND.E.128 | Group set and equal zero hexlet |
| G.SET.AND.NE.8 | Group set and not equal zero bytes |
| G.SET.AND.NE.16 | Group set and not equal zero doublets |
| G.SET.AND.NE.32 | Group set and not equal zero quadlets |
| G.SET.AND.NE.64 | Group set and not equal zero octlets |
| G.SET.AND.NE.128 | Group set and not equal zero hexlet |
| G.SET.E.8 | Group set equal bytes |
| G.SET.E.16 | Group set equal doublets |
| G.SET.E.32 | Group set equal quadlets |
| G.SET.E.64 | Group set equal octlets |
| G.SET.E.128 | Group set equal hexlet |
| G.SET.GE.8 | Group set greater equal signed bytes |
| G.SET.GE.16 | Group set greater equal signed doublets |
| G.SET.GE.32 | Group set greater equal signed quadlets |
| G.SET.GE.64 | Group set greater equal signed octlets |
| G.SET.GE.128 | Group set greater equal signed hexlet |
| G.SET.GE.U.8 | Group set greater equal unsigned bytes |
| G.SET.GE.U.16 | Group set greater equal unsigned doublets |
| G.SET.GE.U.32 | Group set greater equal unsigned quadlets |
| G.SET.GE.U.64 | Group set greater equal unsigned octlets |
| G.SET.GE.U.128 | Group set greater equal unsigned hexlet |
| G.SET.L.8 | Group set signed less bytes |
| G.SET.L.16 | Group set signed less doublets |
| G.SET.L.32 | Group set signed less quadlets |
| G.SET.L.64 | Group set signed less octlets |
| G.SET.L.128 | Group set signed less hexlet |
| G.SET.L.U.8 | Group set less unsigned bytes |
| G.SET.L.U.16 | Group set less unsigned doublets |
| G.SET.L.U.32 | Group set less unsigned quadlets |
| G.SET.L.U.64 | Group set less unsigned octlets |
| G.SET.L.U.128 | Group set less unsigned hexlet |
| G.SET.NE.8 | Group set not equal bytes |
| G.SET.NE.16 | Group set not equal doublets |

Fig. 33A

| | |
|---------------|---|
| G.SET.NE.32 | Group set not equal quadlets |
| G.SET.NE.64 | Group set not equal octlets |
| G.SET.NE.128 | Group set not equal hexlet |
| G.SUB.8 | Group subtract bytes |
| G.SUB.8.O | Group subtract signed bytes check overflow |
| G.SUB.16 | Group subtract doublets |
| G.SUB.16.O | Group subtract signed doublets check overflow |
| G.SUB.32 | Group subtract quadlets |
| G.SUB.32.O | Group subtract signed quadlets check overflow |
| G.SUB.64 | Group subtract octlets |
| G.SUB.64.O | Group subtract signed octlets check overflow |
| G.SUB.128 | Group subtract hexlet |
| G.SUB.128.O | Group subtract signed hexlet check overflow |
| G.SUB.L.8 | Group subtract limit signed bytes |
| G.SUB.L.16 | Group subtract limit signed doublets |
| G.SUB.L.32 | Group subtract limit signed quadlets |
| G.SUB.L.64 | Group subtract limit signed octlets |
| G.SUB.L.128 | Group subtract limit signed hexlet |
| G.SUB.L.U.8 | Group subtract limit unsigned bytes |
| G.SUB.L.U.16 | Group subtract limit unsigned doublets |
| G.SUB.L.U.32 | Group subtract limit unsigned quadlets |
| G.SUB.L.U.64 | Group subtract limit unsigned octlets |
| G.SUB.L.U.128 | Group subtract limit unsigned hexlet |
| G.SUB.U.8.O | Group subtract unsigned bytes check overflow |
| G.SUB.U.16.O | Group subtract unsigned doublets check overflow |
| G.SUB.U.32.O | Group subtract unsigned quadlets check overflow |
| G.SUB.U.64.O | Group subtract unsigned octlets check overflow |
| G.SUB.U.128.O | Group subtract unsigned hexlet check overflow |

Fig. 33A (cont'd)

Equivalencies

| | |
|----------------|--|
| G.SET.E.Z.8 | Group set equal zero bytes |
| G.SET.E.Z.16 | Group set equal zero doublets |
| G.SET.E.Z.32 | Group set equal zero quadlets |
| G.SET.E.Z.64 | Group set equal zero octlets |
| G.SET.E.Z.128 | Group set equal zero hexlet |
| G.SET.G.Z.8 | Group set greater zero signed bytes |
| G.SET.G.Z.16 | Group set greater zero signed doublets |
| G.SET.G.Z.32 | Group set greater zero signed quadlets |
| G.SET.G.Z.64 | Group set greater zero signed octlets |
| G.SET.G.Z.128 | Group set greater zero signed hexlet |
| G.SET.GE.Z.8 | Group set greater equal zero signed bytes |
| G.SET.GE.Z.16 | Group set greater equal zero signed doublets |
| G.SET.GE.Z.32 | Group set greater equal zero signed quadlets |
| G.SET.GE.Z.64 | Group set greater equal zero signed octlets |
| G.SET.GE.Z.128 | Group set greater equal zero signed hexlet |
| G.SET.L.Z.8 | Group set less zero signed bytes |
| G.SET.L.Z.16 | Group set less zero signed doublets |
| G.SET.L.Z.32 | Group set less zero signed quadlets |
| G.SET.L.Z.64 | Group set less zero signed octlets |
| G.SET.L.Z.128 | Group set less zero signed hexlet |
| G.SET.LE.Z.8 | Group set less equal zero signed bytes |
| G.SET.LE.Z.16 | Group set less equal zero signed doublets |
| G.SET.LE.Z.32 | Group set less equal zero signed quadlets |
| G.SET.LE.Z.64 | Group set less equal zero signed octlets |
| G.SET.LE.Z.128 | Group set less equal zero signed hexlet |
| G.SET.NE.Z.8 | Group set not equal zero bytes |
| G.SET.NE.Z.16 | Group set not equal zero doublets |
| G.SET.NE.Z.32 | Group set not equal zero quadlets |
| G.SET.NE.Z.64 | Group set not equal zero octlets |
| G.SET.NE.Z.128 | Group set not equal zero hexlet |

Fig. 33A (cont'd)

| | |
|-----------------------|--|
| <i>G.SET.LE.8</i> | Group set less equal signed bytes |
| <i>G.SET.LE.16</i> | Group set less equal signed doublets |
| <i>G.SET.LE.32</i> | Group set less equal signed quadlets |
| <i>G.SET.LE.64</i> | Group set less equal signed octlets |
| <i>G.SET.LE.128</i> | Group set less equal signed hexlet |
| <i>G.SET.LE.U.8</i> | Group set less equal unsigned bytes |
| <i>G.SET.LE.U.16</i> | Group set less equal unsigned doublets |
| <i>G.SET.LE.U.32</i> | Group set less equal unsigned quadlets |
| <i>G.SET.LE.U.64</i> | Group set less equal unsigned octlets |
| <i>G.SET.LE.U.128</i> | Group set less equal unsigned hexlet |
| <i>G.SET.G.8</i> | Group set signed greater bytes |
| <i>G.SET.G.16</i> | Group set signed greater doublets |
| <i>G.SET.G.32</i> | Group set signed greater quadlets |
| <i>G.SET.G.64</i> | Group set signed greater octlets |
| <i>G.SET.G.128</i> | Group set signed greater hexlet |
| <i>G.SET.G.U.8</i> | Group set greater unsigned bytes |
| <i>G.SET.G.U.16</i> | Group set greater unsigned doublets |
| <i>G.SET.G.U.32</i> | Group set greater unsigned quadlets |
| <i>G.SET.G.U.64</i> | Group set greater unsigned octlets |
| <i>G.SET.G.U.128</i> | Group set greater unsigned hexlet |

| | |
|---------------------------------|-------------------------------------|
| <i>G.SET.E.Z.size rd=rc</i> | ← <i>G.SET.AND.E.size rd=rc,rc</i> |
| <i>G.SET.G.Z.size rd=rc</i> | ← <i>G.SET.L.U.size rd=rc,rc</i> |
| <i>G.SET.GE.Z.size rd=rc</i> | ← <i>G.SET.GE.size rd=rc,rc</i> |
| <i>G.SET.L.Z.size rd=rc</i> | ← <i>G.SET.L.size rd=rc,rc</i> |
| <i>G.SET.LE.Z.size rd=rc</i> | ← <i>G.SET.GE.U.size rd=rc,rc</i> |
| <i>G.SET.NE.Z.size rd=rc</i> | ← <i>G.SET.AND.NE.size rd=rc,rc</i> |
| <i>G.SET.G.size rd=rb,rc</i> | → <i>G.SET.L.size rd=rc,rb</i> |
| <i>G.SET.G.U.size rd=rb,rc</i> | → <i>G.SET.L.U.size rd=rc,rb</i> |
| <i>G.SET.LE.size rd=rb,rc</i> | → <i>G.SET.GE.size rd=rc,rb</i> |
| <i>G.SET.LE.U.size rd=rb,rc</i> | → <i>G.SET.GE.U.size rd=rc,rb</i> |

Fig. 33A (cont'd)

Format

G.op.size rd=rb,rc

rd=gopsize(rb,rc)




Fig. 33B

Definition

```

def GroupReversed(op,size,rd,rc,rb)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  case op of
    G.SUB:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow b_{i+size-1..i} - c_{i+size-1..i}$ 
      endfor
    G.SUB.L:
      for i ← 0 to 128-size by size
         $t \leftarrow (b_{i+size-1} \parallel b_{i+size-1..i}) - (c_{i+size-1} \parallel c_{i+size-1..i})$ 
         $a_{i+size-1..i} \leftarrow (t_{size} \neq t_{size-1}) ? (t_{size} \parallel t_{size-1}^{size-1}) : t_{size-1..0}$ 
      endfor
    G.SUB.LU:
      for i ← 0 to 128-size by size
         $t \leftarrow (0^1 \parallel b_{i+size-1..i}) - (0^1 \parallel c_{i+size-1..i})$ 
         $a_{i+size-1..i} \leftarrow (t_{size} \neq 0) ? 0^{size} : t_{size-1..0}$ 
      endfor
    G.SUB.O:
      for i ← 0 to 128-size by size
         $t \leftarrow (b_{i+size-1} \parallel b_{i+size-1..i}) - (c_{i+size-1} \parallel c_{i+size-1..i})$ 
        if  $(t_{size} \neq t_{size-1})$  then
          raise FixedPointArithmetic
        endif
         $a_{i+size-1..i} \leftarrow t_{size-1..0}$ 
      endfor
    G.SUB.U.O:
      for i ← 0 to 128-size by size
         $t \leftarrow (0^1 \parallel b_{i+size-1..i}) - (0^1 \parallel c_{i+size-1..i})$ 
        if  $(t_{size} \neq 0)$  then
          raise FixedPointArithmetic
        endif
         $a_{i+size-1..i} \leftarrow t_{size-1..0}$ 
      endfor
    G.SET.E:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow (b_{i+size-1..i} = c_{i+size-1..i})^{size}$ 
      endfor
    G.SET.NE:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow (b_{i+size-1..i} \neq c_{i+size-1..i})^{size}$ 
      endfor
    G.SET.AND.E:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((b_{i+size-1..i} \text{ and } c_{i+size-1..i}) = 0)^{size}$ 
      endfor
  endcase
enddef

```

Fig. 33C

```

G.SET.AND.NE:
  for i ← 0 to 128-size by size
    ai+size-1..i ← ((bi+size-1..i and ci+size-1..i) ≠ 0)size
  endfor
G.SET.L:
  for i ← 0 to 128-size by size
    ai+size-1..i ← ((rc = rb) ? (bi+size-1..i < 0) : (bi+size-1..i < ci+size-1..i))size
  endfor
G.SET.GE:
  for i ← 0 to 128-size by size
    ai+size-1..i ← ((rc = rb) ? (bi+size-1..i ≥ 0) : (bi+size-1..i ≥ ci+size-1..i))size
  endfor
G.SET.L.U:
  for i ← 0 to 128-size by size
    ai+size-1..i ← ((rc = rb) ? (bi+size-1..i > 0) :
      ((0 || bi+size-1..i) < (0 || ci+size-1..i)))size
  endfor
G.SET.GE.U:
  for i ← 0 to 128-size by size
    ai+size-1..i ← ((rc = rb) ? (bi+size-1..i ≤ 0) :
      ((0 || bi+size-1..i) ≥ (0 || ci+size-1..i)))size
  endfor
endcase
RegWrite(rd, 128, a)
enddef

```

Exceptions

Fixed-point arithmetic

Fig. 33C (cont'd)

| | |
|----------------|---|
| E.DIV.64 | Ensemble divide signed octlets |
| E.DIV.U.64 | Ensemble divide unsigned octlets |
| E.MUL.8 | Ensemble multiply signed bytes |
| E.MUL.16 | Ensemble multiply signed doublets |
| E.MUL.32 | Ensemble multiply signed quadlets |
| E.MUL.64 | Ensemble multiply signed octlets |
| E.MUL.SUM.8 | Ensemble multiply sum signed bytes |
| E.MUL.SUM.16 | Ensemble multiply sum signed doublets |
| E.MUL.SUM.32 | Ensemble multiply sum signed quadlets |
| E.MUL.SUM.64 | Ensemble multiply sum signed octlets |
| E.MUL.C.8 | Ensemble complex multiply bytes |
| E.MUL.C.16 | Ensemble complex multiply doublets |
| E.MUL.C.32 | Ensemble complex multiply quadlets |
| E.MUL.M.8 | Ensemble multiply mixed-signed bytes |
| E.MUL.M.16 | Ensemble multiply mixed-signed doublets |
| E.MUL.M.32 | Ensemble multiply mixed-signed quadlets |
| E.MUL.M.64 | Ensemble multiply mixed-signed octlets |
| E.MUL.P.8 | Ensemble multiply polynomial bytes |
| E.MUL.P.16 | Ensemble multiply polynomial doublets |
| E.MUL.P.32 | Ensemble multiply polynomial quadlets |
| E.MUL.P.64 | Ensemble multiply polynomial octlets |
| E.MUL.SUM.C.8 | Ensemble multiply sum complex bytes |
| E.MUL.SUM.C.16 | Ensemble multiply sum complex doublets |
| E.MUL.SUM.C.32 | Ensemble multiply sum complex quadlets |
| E.MUL.SUM.M.8 | Ensemble multiply sum mixed-signed bytes |
| E.MUL.SUM.M.16 | Ensemble multiply sum mixed-signed doublets |
| E.MUL.SUM.M.32 | Ensemble multiply sum mixed-signed quadlets |
| E.MUL.SUM.M.64 | Ensemble multiply sum mixed-signed octlets |
| E.MUL.SUM.U.8 | Ensemble multiply sum unsigned bytes |
| E.MUL.SUM.U.16 | Ensemble multiply sum unsigned doublets |
| E.MUL.SUM.U.32 | Ensemble multiply sum unsigned quadlets |
| E.MUL.SUM.U.64 | Ensemble multiply sum unsigned octlets |
| E.MUL.U.8 | Ensemble multiply unsigned bytes |
| E.MUL.U.16 | Ensemble multiply unsigned doublets |
| E.MUL.U.32 | Ensemble multiply unsigned quadlets |
| E.MUL.U.64 | Ensemble multiply unsigned octlets |

Fig. 34A

Format

E.op.size rd=rc,rb

rd=eopsize(rc,rb)




Fig. 34B

Definition

```

def mul(size,h,vs,v,i,ws,w,j) as
    mul ← ((vs&vsize-1+i)h-size || vsize-1+i..i) * ((ws&wsize-1+j)h-size || wsize-1+j..j)
enddef

def c ← PolyMultiply(size,a,b) as
    p[0] ← 02*size
    for k ← 0 to size-1
        p[k+1] ← p[k] ^ ak ? (0size-k || b || 0k) : 02*size
    endfor
    c ← p[size]
enddef

def Ensemble(op,size,rd,rc,rb)
    c ← RegRead(rc, 128)
    b ← RegRead(rb, 128)
    case op of
        E.MUL., E.MUL.C., EMUL.SUM, E.MUL.SUM.C, E.CON, E.CON.C, E.DIV:
            cs ← bs ← 1
        E.MUL.M., EMUL.SUM.M, E.CON.M:
            cs ← 0
            bs ← 1
        E.MUL.U., EMUL.SUM.U, E.CON.U, E.DIV.U, E.MUL.P:
            cs ← bs ← 0
    endcase
    case op of
        E.MUL, E.MUL.U, E.MUL.M:
            for i ← 0 to 64-size by size
                d2*(i+size)-1..2*i ← mul(size,2*size,cs,c,i,bs,b,i)
            endfor
        E.MUL.P:
            for i ← 0 to 64-size by size
                d2*(i+size)-1..2*i ← PolyMultiply(size,csize-1+i..i,bsize-1+i..i)
            endfor
        E.MUL.C:
            for i ← 0 to 64-size by size
                if (i and size) = 0 then
                    p ← mul(size,2*size,1,c,i,1,b,i) - mul(size,2*size,1,c,i+size,1,b,i+size)
                else
                    p ← mul(size,2*size,1,c,i,1,b,i+size) + mul(size,2*size,1,c,i,1,b,i+size)
                endif
                d2*(i+size)-1..2*i ← p
            endfor
        E.MUL.SUM, E.MUL.SUM.U, E.MUL.SUM.M:
            p[0] ← 0128
            for i ← 0 to 128-size by size
                p[i+size] ← p[i] + mul(size,128,cs,c,i,bs,b,i)
            endfor
            a ← p[128]
        E.MUL.SUM.C:
            p[0] ← 064
            p[size] ← 064
            for i ← 0 to 128-size by size
                if (i and size) = 0 then
                    p[i+size] ← p[i] + mul(size,64,1,c,i,1,b,i)
                    - mul(size,64,1,c,i+size,1,b,i+size)
                else
                    p[i+2*size] ← p[i] + mul(size,64,1,c,i,1,b,i+size)
                    + mul(size,64,1,c,i+size,1,b,i)
                endif
            endfor
            a ← p[128+size] || p[128]
    endcase
enddef

```

Fig. 34C

```

E.CON, E.CON.U, E.CON.M:
    p[0] ← 0128
    for j ← 0 to 64-size by size
        for i ← 0 to 64-size by size
            p[j+size]2*(i+size)-1..2*i ← p[j]2*(i+size)-1..2*i +
                mul(size, 2*size, cs, c, i+64-j, bs, b, j)
        endfor
    endfor
    a ← p[64]
E.CON.C:
    p[0] ← 0128
    for j ← 0 to 64-size by size
        for i ← 0 to 64-size by size
            if ((-i) and j and size) = 0 then
                p[j+size]2*(i+size)-1..2*i ← p[j]2*(i+size)-1..2*i +
                    mul(size, 2*size, 1, c, i+64-j, 1, b, j)
            else
                p[j+size]2*(i+size)-1..2*i ← p[j]2*(i+size)-1..2*i -
                    mul(size, 2*size, 1, c, i+64-j+2*size, 1, b, j)
            endif
        endfor
    endfor
    a ← p[64]
E.DIV:
    if (b = 0) or ( (c = (1||063)) and (b = 164) ) then
        a ← undefined
    else
        q ← c / b
        r ← c - q*b
        a ← r63..0 || q63..0
    endif
E.DIV.U:
    if b = 0 then
        a ← undefined
    else
        q ← (0 || c) / (0 || b)
        r ← c - (0 || q)*(0 || b)
        a ← r63..0 || q63..0
    endif
endcase
RegWrite(rd, 128, a)
enddef

```

Exceptions

none

Fig. 34C (cont'd)

| | |
|------------------|---|
| G.COM.AND.E.8 | Group compare and equal zero bytes |
| G.COM.AND.E.16 | Group compare and equal zero doublets |
| G.COM.AND.E.32 | Group compare and equal zero quadlets |
| G.COM.AND.E.64 | Group compare and equal zero octlets |
| G.COM.AND.E.128 | Group compare and equal zero hexlet |
| G.COM.AND.NE.8 | Group compare and not equal zero bytes |
| G.COM.AND.NE.16 | Group compare and not equal zero doublets |
| G.COM.AND.NE.32 | Group compare and not equal zero quadlets |
| G.COM.AND.NE.64 | Group compare and not equal zero octlets |
| G.COM.AND.NE.128 | Group compare and not equal zero hexlet |
| G.COM.E.8 | Group compare equal bytes |
| G.COM.E.16 | Group compare equal doublets |
| G.COM.E.32 | Group compare equal quadlets |
| G.COM.E.64 | Group compare equal octlets |
| G.COM.E.128 | Group compare equal hexlet |
| G.COM.GE.8 | Group compare greater equal signed bytes |
| G.COM.GE.16 | Group compare greater equal signed doublets |
| G.COM.GE.32 | Group compare greater equal signed quadlets |
| G.COM.GE.64 | Group compare greater equal signed octlets |
| G.COM.GE.128 | Group compare greater equal signed hexlet |
| G.COM.GE.U.8 | Group compare greater equal unsigned bytes |
| G.COM.GE.U.16 | Group compare greater equal unsigned doublets |
| G.COM.GE.U.32 | Group compare greater equal unsigned quadlets |
| G.COM.GE.U.64 | Group compare greater equal unsigned octlets |
| G.COM.GE.U.128 | Group compare greater equal unsigned hexlet |
| G.COM.L.8 | Group compare signed less bytes |
| G.COM.L.16 | Group compare signed less doublets |
| G.COM.L.32 | Group compare signed less quadlets |
| G.COM.L.64 | Group compare signed less octlets |
| G.COM.L.128 | Group compare signed less hexlet |
| G.COM.L.U.8 | Group compare less unsigned bytes |
| G.COM.L.U.16 | Group compare less unsigned doublets |
| G.COM.L.U.32 | Group compare less unsigned quadlets |
| G.COM.L.U.64 | Group compare less unsigned octlets |
| G.COM.L.U.128 | Group compare less unsigned hexlet |
| G.COM.NE.8 | Group compare not equal bytes |
| G.COM.NE.16 | Group compare not equal doublets |
| G.COM.NE.32 | Group compare not equal quadlets |
| G.COM.NE.64 | Group compare not equal octlets |
| G.COM.NE.128 | Group compare not equal hexlet |

Fig. 35A

Format

G.COM.op.size rd,rc
G.COM.opz.size rcd

gcomopsize(rd,rc)




Fig. 35B

Definition

```
def GroupCompare(op,size,rd,rc)
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  case op of
    G.COM.E:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow (d_{i+size-1..i} = c_{i+size-1..i})^{size}$ 
      endfor
    G.COM.NE:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow (d_{i+size-1..i} \neq c_{i+size-1..i})^{size}$ 
      endfor
    G.COM.AND.E:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((c_{i+size-1..i} \text{ and } d_{i+size-1..i}) = 0)^{size}$ 
      endfor
    G.COM.AND.NE:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((c_{i+size-1..i} \text{ and } d_{i+size-1..i}) \neq 0)^{size}$ 
      endfor
    G.COM.L:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((rd = rc) ? (c_{i+size-1..i} < 0) : (d_{i+size-1..i} < c_{i+size-1..i}))^{size}$ 
      endfor
    G.COM.GE:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((rd = rc) ? (c_{i+size-1..i} \geq 0) : (d_{i+size-1..i} \geq c_{i+size-1..i}))^{size}$ 
      endfor
    G.COM.L.U:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((rd = rc) ? (c_{i+size-1..i} > 0) :$   

             $((0 \parallel d_{i+size-1..i}) < (0 \parallel c_{i+size-1..i})))^{size}$ 
      endfor
    G.COM.GE.U:
      for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow ((rd = rc) ? (c_{i+size-1..i} \leq 0) :$   

             $((0 \parallel d_{i+size-1..i}) \geq (0 \parallel c_{i+size-1..i})))^{size}$ 
      endfor
  endcase
  if (a ≠ 0) then
    raise FixedPointArithmetic
  endif
enddef
```

Exceptions

Fixed-point arithmetic

Fig. 35C

| | |
|------------------|--|
| E.LOG.MOST.8 | Ensemble log of most significant bit signed bytes |
| E.LOG.MOST.16 | Ensemble log of most significant bit signed doublets |
| E.LOG.MOST.32 | Ensemble log of most significant bit signed quadlets |
| E.LOG.MOST.64 | Ensemble log of most significant bit signed octlets |
| E.LOG.MOST.128 | Ensemble log of most significant bit signed hexlet |
| E.LOG.MOST.U.8 | Ensemble log of most significant bit unsigned bytes |
| E.LOG.MOST.U.16 | Ensemble log of most significant bit unsigned doublets |
| E.LOG.MOST.U.32 | Ensemble log of most significant bit unsigned quadlets |
| E.LOG.MOST.U.64 | Ensemble log of most significant bit unsigned octlets |
| E.LOG.MOST.U.128 | Ensemble log of most significant bit unsigned hexlet |
| E.SUM.8 | Ensemble sum signed bytes |
| E.SUM.16 | Ensemble sum signed doublets |
| E.SUM.32 | Ensemble sum signed quadlets |
| E.SUM.64 | Ensemble sum signed octlets |
| E.SUM.U.1 | Ensemble sum unsigned bits |
| E.SUM.U.8 | Ensemble sum unsigned bytes |
| E.SUM.U.16 | Ensemble sum unsigned doublets |
| E.SUM.U.32 | Ensemble sum unsigned quadlets |
| E.SUM.U.64 | Ensemble sum unsigned octlets |

Selection

| class | op | size |
|--------------------------|---------------------|----------------|
| sum | SUM | 8 16 32 64 |
| | SUM.U | 1 8 16 32 64 |
| log most significant bit | LOG.MOST LOG.MOST.U | 8 16 32 64 128 |

Fig. 36A

Format

E.op.size rd=rc

rd=eopsize(rc)




Fig. 36B

Definition

```
def EnsembleUnary(op,size,rd,rc)
  c ← RegRead(rc, 128)
  case op of
    E.LOG.MOST:
      for i ← 0 to 128-size by size
        if (ci+size-1..i = 0) then
          ai+size-1..i ← -1
        else
          for j ← 0 to size-1
            if csize-1+i..j+i = (csize-1-j || not csize-1+i) then
              ai+size-1..i ← j
            endif
          endfor
        endif
      endfor
    E.LOG.MOSTU:
      for i ← 0 to 128-size by size
        if (ci+size-1..i = 0) then
          ai+size-1..i ← -1
        else
          for j ← 0 to size-1
            if csize-1+i..j+i = (0size-1-j || 1) then
              ai+size-1..i ← j
            endif
          endfor
        endif
      endfor
    E.SUM:
      p[0] ← 0128
      for i ← 0 to 128-size by size
        p[i+size] ← p[i] + (csize-1+i || csize-1+i..i)
      endfor
      a ← p[128]
    E.SUMU:
      p[0] ← 0128
      for i ← 0 to 128-size by size
        p[i+size] ← p[i] + (0128-size || csize-1+i..i)
      endfor
      a ← p[128]
  endcase
  RegWrite(rd, 128, a)
enddef
```

Exceptions

none

Fig. 36C

Floating-point function Definitions

```
def eb ← ebits(prec) as
  case pref of
    16:
      eb ← 5
    32:
      eb ← 8
    64:
      eb ← 11
    128:
      eb ← 15
  endcase
enddef

def eb ← ebias(prec) as
  eb ← 0 || 1ebits(prec)-1
enddef

def fb ← fbits(prec) as
  fb ← prec - 1 - eb
enddef

def a ← F(prec, ai) as
  a.s ← aiprec-1
  ae ← aiprec-2..fbits(prec)
  af ← aifbits(prec)-1..0
  if ae = 1ebits(prec) then
    if af = 0 then
      a.t ← INFINITY
    elseif afbits(prec)-1 then
      a.t ← SNaN
      a.e ← -fbits(prec)
      a.f ← 1 || afbits(prec)-2..0
    else
      a.t ← QNaN
      a.e ← -fbits(prec)
      a.f ← af
    endif
  endif
```

Fig. 37

```

elseif ae = 0 then
  if af = 0 then
    a.t ← ZERO
  else
    a.t ← NORM
    a.e ← 1-ebias(prec)-fbits(prec)
    a.f ← 0 || af
  endif
else
  a.t ← NORM
  a.e ← ae-ebias(prec)-fbits(prec)
  a.f ← 1 || af
endif
enddef

def a ← DEFAULTQNAN as
  a.s ← 0
  a.t ← QNAN
  a.e ← -1
  a.f ← 1
enddef

def a ← DEFAULTSNAN as
  a.s ← 0
  a.t ← SNAN
  a.e ← -1
  a.f ← 1
enddef

def fadd(a,b) as faddr(a,b,N) enddef

def c ← faddr(a,b,round) as
  if a.t=NORM and b.t=NORM then
    // d,e are a,b with exponent aligned and fraction adjusted
    if a.e > b.e then
      d ← a
      e.t ← b.t
      e.s ← b.s
      e.e ← a.e
      e.f ← b.f || 0a.e-b.e
    else if a.e < b.e then
      d.t ← a.t
      d.s ← a.s
      d.e ← b.e
      d.f ← a.f || 0b.e-a.e
      e ← b
    endif
    c.t ← d.t
    c.e ← d.e
    if d.s = e.s then
      c.s ← d.s
      c.f ← d.f + e.f
    elseif d.f > e.f then
      c.s ← d.s
      c.f ← d.f - e.f
    else
      c.s ← d.s
      c.f ← d.f
    endif
  else
    // ... (other cases for NaN, Zero, etc.)
  endif
enddef

```

Fig. 37 (cont'd)

```

        elseif d.f < e.f then
            c.s ← e.s
            c.f ← e.f - d.f
        else
            c.s ← r=F
            c.t ← ZERO
        endif
    // priority is given to b operand for NaN propagation
    elseif (b.t=SNAN) or (b.t=QNaN) then
        c ← b
    elseif (a.t=SNAN) or (a.t=QNaN) then
        c ← a
    elseif a.t=ZERO and b.t=ZERO then
        c.t ← ZERO
        c.s ← (a.s and b.s) or (round=F and (a.s or b.s))
    // NULL values are like zero, but do not combine with ZERO to alter sign
    elseif a.t=ZERO or a.t=NULL then
        c ← b
    elseif b.t=ZERO or b.t=NULL then
        c ← a
    elseif a.t=INFINITY and b.t=INFINITY then
        if a.s ≠ b.s then
            c ← DEFAULTSNAN // Invalid
        else
            c ← a
        endif
    elseif a.t=INFINITY then
        c ← a
    elseif b.t=INFINITY then
        c ← b
    else
        assert FALSE // should have covered al the cases above
    endif
enddef

def b ← fneg(a) as
    b.s ← ~a.s
    b.t ← a.t
    b.e ← a.e
    b.f ← a.f
enddef

def fsub(a,b) as fsubr(a,b,N) enddef

def fsubr(a,b,round) as faddr(a,fneg(b),round) enddef

def frsub(a,b) as frsubr(a,b,N) enddef

def frsubr(a,b,round) as faddr(fneg(a),b,round) enddef

def c ← fcom(a,b) as
    if (a.t=SNAN) or (a.t=QNaN) or (b.t=SNAN) or (b.t=QNaN) then
        c ← U
    elseif a.t=INFINITY and b.t=INFINITY then
        if a.s ≠ b.s then
            c ← (a.s=0) ? G: L

```

Fig. 37 (c nt'd)

```

        else
            c ← E
        endif
    elseif a.t=INFINITY then
        c ← (a.s=0) ? G: L
    elseif b.t=INFINITY then
        c ← (b.s=0) ? G: L
    elseif a.t=NORM and b.t=NORM then
        if a.s ≠ b.s then
            c ← (a.s=0) ? G: L
        else
            if a.e > b.e then
                af ← a.f
                bf ← b.f || 0a.e-b.e
            else
                af ← a.f || 0b.e-a.e
                bf ← b.f
            endif
            if af = bf then
                c ← E
            else
                c ← ((a.s=0) ^ (af > bf)) ? G : L
            endif
        endif
    elseif a.t=NORM then
        c ← (a.s=0) ? G: L
    elseif b.t=NORM then
        c ← (b.s=0) ? G: L
    elseif a.t=ZERO and b.t=ZERO then
        c ← E
    else
        assert FALSE // should have covered all the cases above
    endif
enddef

def c ← fmul(a,b) as
    if a.t=NORM and b.t=NORM then
        c.s ← a.s ^ b.s
        c.t ← NORM
        c.e ← a.e + b.e
        c.f ← a.f * b.f
        // priority is given to b operand for NaN propagation
    elseif (b.t=SNAN) or (b.t=QNAN) then
        c.s ← a.s ^ b.s
        c.t ← b.t
        c.e ← b.e
        c.f ← b.f
    elseif (a.t=SNAN) or (a.t=QNAN) then
        c.s ← a.s ^ b.s
        c.t ← a.t
        c.e ← a.e
        c.f ← a.f
    elseif a.t=ZERO and b.t=INFINITY then
        c ← DEFAULTSNAN // Invalid
    elseif a.t=INFINITY and b.t=ZERO then
        c ← DEFAULTSNAN // Invalid

```

Fig. 37 (cont'd)


```

elseif a.t=ZERO or b.t=ZERO then
    c.s ← a.s ^ b.s
    c.t ← ZERO
else
    assert FALSE // should have covered al the cases above
endif
enddef

def c ← fdivr(a,b) as
    if a.t=NORM and b.t=NORM then
        c.s ← a.s ^ b.s
        c.t ← NORM
        c.e ← a.e - b.e + 256
        c.f ← (a.f || 0256) / b.f
        // priority is given to b operand for NaN propagation
    elseif (b.t=SNAN) or (b.t=QNAN) then
        c.s ← a.s ^ b.s
        c.t ← b.t
        c.e ← b.e
        c.f ← b.f
    elseif (a.t=SNAN) or (a.t=QNAN) then
        c.s ← a.s ^ b.s
        c.t ← a.t
        c.e ← a.e
        c.f ← a.f
    elseif a.t=ZERO and b.t=ZERO then
        c ← DEFAULTSNAN // Invalid
    elseif a.t=INFINITY and b.t=INFINITY then
        c ← DEFAULTSNAN // Invalid
    elseif a.t=ZERO then
        c.s ← a.s ^ b.s
        c.t ← ZERO
    elseif a.t=INFINITY then
        c.s ← a.s ^ b.s
        c.t ← INFINITY
    else
        assert FALSE // should have covered al the cases above
    endif
enddef

def msb ← findmsb(a) as
    MAXF ← 218 // Largest possible f value after matrix multiply
    for j ← 0 to MAXF
        if aMAXF-1..j = (0MAXF-1-j || 1) then
            msb ← j
        endif
    endfor
enddef

def ai ← PackF(prec,a,round) as
    case a.t of
        NORM:
            msb ← findmsb(a.f)
            rn ← msb-1-fbits(prec) // lsb for normal
            rd ← -ebias(prec)-a.e-1-fbits(prec) // lsb if a denormal
            rb ← (rn > rd) ? rn : rd
    endcase
enddef

```

Fig. 37 (cont'd)

```

if rb ≤ 0 then
    aifr ← a.fmsb-1..0 || 0-rb
    eadj ← 0
else
    case round of
        C:
            s ← 0msb-rb || (~a.s)rb
        F:
            s ← 0msb-rb || (a.s)rb
        N, NONE:
            s ← 0msb-rb || ~a.frb || a.frbrb-1
        X:
            if a.frb-1..0 ≠ 0 then
                raise FloatingPointArithmetic // Inexact
            endif
            s ← 0
        Z:
            s ← 0
    endcase
    v ← (0 || a.fmsb..0) + (0 || s)
    if vmsb = 1 then
        aifr ← vmsb-1..rb
        eadj ← 0
    else
        aifr ← 0fbits(prec)
        eadj ← 1
    endif
endif
aien ← a.e + msb - 1 + eadj + ebias(prec)
if aien ≤ 0 then
    if round = NONE then
        ai ← a.s || 0ebits(prec) || aifr
    else
        raise FloatingPointArithmetic // Underflow
    endif
elseif aien ≥ 1ebits(prec) then
    if round = NONE then
        //default: round-to-nearest overflow handling
        ai ← a.s || 1ebits(prec) || 0fbits(prec)
    else
        raise FloatingPointArithmetic // Underflow
    endif
else
    ai ← a.s || aienebits(prec)-1..0 || aifr
endif
SNAN:
    if round ≠ NONE then
        raise FloatingPointArithmetic // Invalid
    endif
    if -a.e < fbits(prec) then
        ai ← a.s || 1ebits(prec) || a.f-a.e-1..0 || 0fbits(prec)+a.e
    endif

```

Fig. 37 (cont'd)

```

else
    lsb ← a.f.a.e-1-fbits(prec)+1..0 ≠ 0
    ai ← a.s || 1ebits(prec) || a.f-a.e-1..-a.e-1-fbits(prec)+2 || lsb
endif
QNAN:
    if -a.e < fbits(prec) then
        ai ← a.s || 1ebits(prec) || a.f-a.e-1..0 || 0fbits(prec)+a.e
    else
        lsb ← a.f.a.e-1-fbits(prec)+1..0 ≠ 0
        ai ← a.s || 1ebits(prec) || a.f-a.e-1..-a.e-1-fbits(prec)+2 || lsb
    endif
ZERO:
    ai ← a.s || 0ebits(prec) || 0fbits(prec)
INFINITY:
    ai ← a.s || 1ebits(prec) || 0fbits(prec)
endcase
defdef
def ai ← fsinkr(prec, a, round) as
    case a.t of
        NORM:
            msb ← findmsb(a.f)
            rb ← -a.e
            if rb ≤ 0 then
                aifr ← a.fmsb..0 || 0-rb
                aims ← msb - rb
            else
                case round of
                    C, C.D:
                        s ← 0msb-rb || (~ai.s)rb
                    F, F.D:
                        s ← 0msb-rb || (ai.s)rb
                    N, NONE:
                        s ← 0msb-rb || ~ai.frb || ai.frb-1
                    X:
                        if ai.frb-1..0 ≠ 0 then
                            raise FloatingPointArithmetic // Inexact
                        endif
                        s ← 0
                    Z, Z.D:
                        s ← 0
                endcase
                v ← (0||a.fmsb..0) + (0||s)
                if vmsb = 1 then
                    aims ← msb + 1 - rb
                else
                    aims ← msb - rb
                endif
                aifr ← vaims..rb
            endif
            if aims > prec then
                case round of
                    C.D, F.D, NONE, Z.D:
                        ai ← a.s || (~as)prec-1

```

Fig. 37 (cont'd)

```

                                C, F, N, X, Z:
                                raise FloatingPointArithmetic // Overflow
                                endcase
                            elseif a.s = 0 then
                                ai ← aifr
                            else
                                ai ← -aifr
                            endif
ZERO:
    ai ← 0prec
SNAN, QNAN:
    case round of
        C.D, F.D, NONE, Z.D:
            ai ← 0prec
        C, F, N, X, Z:
            raise FloatingPointArithmetic // Invalid
    endcase
INFINITY:
    case round of
        C.D, F.D, NONE, Z.D:
            ai ← a.s || (~a.s)prec-1
        C, F, N, X, Z:
            raise FloatingPointArithmetic // Invalid
    endcase
endcase
enddef

def c ← frecrest(a) as
    b.s ← 0
    b.t ← NORM
    b.e ← 0
    b.f ← 1
    c ← fest(fdiv(b,a))
enddef

def c ← frsqrest(a) as
    b.s ← 0
    b.t ← NORM
    b.e ← 0
    b.f ← 1
    c ← fest(fsqr(fdiv(b,a)))
enddef

def c ← fest(a) as
    if (a.t=NORM) then
        msb ← findmsb(a.f)
        a.e ← a.e + msb - 13
        a.f ← a.fmsb..msb-12 || 1
    else
        c ← a
    endif
enddef

def c ← fsqr(a) as
    if (a.t=NORM) and (a.s=0) then
        c.s ← 0
        c.t ← NORM
        if (a.e0 = 1) then

```

Fig. 37 (cont'd)

```

        c.e ← (a.e-127) / 2
        c.f ← sqrt(a.f || 0127)
    else
        c.e ← (a.e-128) / 2
        c.f ← sqrt(a.f || 0128)
    endif
elseif (a.t=SNAN) or (a.t=QNAN) or a.t=ZERO or ((a.t=INFINITY) and (a.s=0)) then
    c ← a
elseif ((a.t=NORM) or (a.t=INFINITY)) and (a.s=1) then
    c ← DEFAULTSNAN // Invalid
else
    assert FALSE // should have covered all the cases above
endif
enddef

```

Fig. 37 (cont'd)

| | |
|---------------|---|
| E.ADD.F.16 | Ensemble add floating-point half |
| E.ADD.F.16.C | Ensemble add floating-point half ceiling |
| E.ADD.F.16.F | Ensemble add floating-point half floor |
| E.ADD.F.16.N | Ensemble add floating-point half nearest |
| E.ADD.F.16.X | Ensemble add floating-point half exact |
| E.ADD.F.16.Z | Ensemble add floating-point half zero |
| E.ADD.F.32 | Ensemble add floating-point single |
| E.ADD.F.32.C | Ensemble add floating-point single ceiling |
| E.ADD.F.32.F | Ensemble add floating-point single floor |
| E.ADD.F.32.N | Ensemble add floating-point single nearest |
| E.ADD.F.32.X | Ensemble add floating-point single exact |
| E.ADD.F.32.Z | Ensemble add floating-point single zero |
| E.ADD.F.64 | Ensemble add floating-point double |
| E.ADD.F.64.C | Ensemble add floating-point double ceiling |
| E.ADD.F.64.F | Ensemble add floating-point double floor |
| E.ADD.F.64.N | Ensemble add floating-point double nearest |
| E.ADD.F.64.X | Ensemble add floating-point double exact |
| E.ADD.F.64.Z | Ensemble add floating-point double zero |
| E.ADD.F.128 | Ensemble add floating-point quad |
| E.ADD.F.128.C | Ensemble add floating-point quad ceiling |
| E.ADD.F.128.F | Ensemble add floating-point quad floor |
| E.ADD.F.128.N | Ensemble add floating-point quad nearest |
| E.ADD.F.128.X | Ensemble add floating-point quad exact |
| E.ADD.F.128.Z | Ensemble add floating-point quad zero |
| E.DIV.F.16 | Ensemble divide floating-point half |
| E.DIV.F.16.C | Ensemble divide floating-point half ceiling |
| E.DIV.F.16.F | Ensemble divide floating-point half floor |
| E.DIV.F.16.N | Ensemble divide floating-point half nearest |
| E.DIV.F.16.X | Ensemble divide floating-point half exact |
| E.DIV.F.16.Z | Ensemble divide floating-point half zero |
| E.DIV.F.32 | Ensemble divide floating-point single |
| E.DIV.F.32.C | Ensemble divide floating-point single ceiling |
| E.DIV.F.32.F | Ensemble divide floating-point single floor |
| E.DIV.F.32.N | Ensemble divide floating-point single nearest |
| E.DIV.F.32.X | Ensemble divide floating-point single exact |
| E.DIV.F.32.Z | Ensemble divide floating-point single zero |
| E.DIV.F.64 | Ensemble divide floating-point double |

Fig. 38A

| | |
|---------------|---|
| E.DIV.F.64.C | Ensemble divide floating-point double ceiling |
| E.DIV.F.64.F | Ensemble divide floating-point double floor |
| E.DIV.F.64.N | Ensemble divide floating-point double nearest |
| E.DIV.F.64.X | Ensemble divide floating-point double exact |
| E.DIV.F.64.Z | Ensemble divide floating-point double zero |
| E.DIV.F.128 | Ensemble divide floating-point quad |
| E.DIV.F.128.C | Ensemble divide floating-point quad ceiling |
| E.DIV.F.128.F | Ensemble divide floating-point quad floor |
| E.DIV.F.128.N | Ensemble divide floating-point quad nearest |
| E.DIV.F.128.X | Ensemble divide floating-point quad exact |
| E.DIV.F.128.Z | Ensemble divide floating-point quad zero |
| E.MUL.C.F.16 | Ensemble multiply complex floating-point half |
| E.MUL.C.F.32 | Ensemble multiply complex floating-point single |
| E.MUL.C.F.64 | Ensemble multiply complex floating-point double |
| E.MUL.F.16 | Ensemble multiply floating-point half |
| E.MUL.F.16.C | Ensemble multiply floating-point half ceiling |
| E.MUL.F.16.F | Ensemble multiply floating-point half floor |
| E.MUL.F.16.N | Ensemble multiply floating-point half nearest |
| E.MUL.F.16.X | Ensemble multiply floating-point half exact |
| E.MUL.F.16.Z | Ensemble multiply floating-point half zero |
| E.MUL.F.32 | Ensemble multiply floating-point single |
| E.MUL.F.32.C | Ensemble multiply floating-point single ceiling |
| E.MUL.F.32.F | Ensemble multiply floating-point single floor |
| E.MUL.F.32.N | Ensemble multiply floating-point single nearest |
| E.MUL.F.32.X | Ensemble multiply floating-point single exact |
| E.MUL.F.32.Z | Ensemble multiply floating-point single zero |
| E.MUL.F.64 | Ensemble multiply floating-point double |
| E.MUL.F.64.C | Ensemble multiply floating-point double ceiling |
| E.MUL.F.64.F | Ensemble multiply floating-point double floor |
| E.MUL.F.64.N | Ensemble multiply floating-point double nearest |
| E.MUL.F.64.X | Ensemble multiply floating-point double exact |
| E.MUL.F.64.Z | Ensemble multiply floating-point double zero |
| E.MUL.F.128 | Ensemble multiply floating-point quad |
| E.MUL.F.128.C | Ensemble multiply floating-point quad ceiling |
| E.MUL.F.128.F | Ensemble multiply floating-point quad floor |
| E.MUL.F.128.N | Ensemble multiply floating-point quad nearest |
| E.MUL.F.128.X | Ensemble multiply floating-point quad exact |
| E.MUL.F.128.Z | Ensemble multiply floating-point quad zero |

Fig. 38A (cont'd)

Selection

| class | op | prec | | | | round/trap |
|------------------|-------------|------|----|----|-----|----------------|
| add | EADDF | 16 | 32 | 64 | 128 | NONE C F N X Z |
| divide | EDIVF | 16 | 32 | 64 | 128 | NONE C F N X Z |
| multiply | EMULF | 16 | 32 | 64 | 128 | NONE C F N X Z |
| complex multiply | EMUL.C F | 16 | 32 | 64 | | NONE |

Format

E.op.prec.round rd=rc,rb

rd=eopprecround(rc,rb)




Fig. 38B

Definition

```
def mul(size,v,i,w,j) as
    mul ← fmul(F(size,vsize-1+i..i),F(size,wsize-1+j..j))
enddef

def EnsembleFloatingPoint(op,prec,round,ra,rb,rc) as
    c ← RegRead(rc, 128)
    b ← RegRead(rb, 128)
    for i ← 0 to 128-prec by prec
        ci ← F(prec,ci+prec-1..i)
        bi ← F(prec,bi+prec-1..i)
        case op of
            E.ADD.F:
                ai ← faddr(ci,bi,round)
            E.MUL.F:
                ai ← fmul(ci,bi)
            E.MUL.C.F:
                if (i and prec) then
                    ai ← fadd(mul(prec,c,i,b,i-prec), mul(prec,c,i-prec,b,i))
                else
                    ai ← fsub(mul(prec,c,i,b,i), mul(prec,c,i+prec,b,i+prec))
                endif
            E.DIV.F.:
                ai ← fdiv(ci,bi)
        endcase
        ai+prec-1..i ← PackF(prec, ai, round)
    endfor
    RegWrite(rd, 128, a)
enddef
```

Exceptions

Floating-point arithmetic

Fig. 38C

Operation codes

| | |
|-------------------|--|
| E.MUL.ADD.C.F.16 | Ensemble multiply add complex floating-point half |
| E.MUL.ADD.C.F.32 | Ensemble multiply add complex floating-point single |
| E.MUL.ADD.C.F.64 | Ensemble multiply add complex floating-point double |
| E.MUL.ADD.F.16 | Ensemble multiply add floating-point half |
| E.MUL.ADD.F.16.C | Ensemble multiply add floating-point half ceiling |
| E.MUL.ADD.F.16.F | Ensemble multiply add floating-point half floor |
| E.MUL.ADD.F.16.N | Ensemble multiply add floating-point half nearest |
| E.MUL.ADD.F.16.X | Ensemble multiply add floating-point half exact |
| E.MUL.ADD.F.16.Z | Ensemble multiply add floating-point half zero |
| E.MUL.ADD.F.32 | Ensemble multiply add floating-point single |
| E.MUL.ADD.F.32.C | Ensemble multiply add floating-point single ceiling |
| E.MUL.ADD.F.32.F | Ensemble multiply add floating-point single floor |
| E.MUL.ADD.F.32.N | Ensemble multiply add floating-point single nearest |
| E.MUL.ADD.F.32.X | Ensemble multiply add floating-point single exact |
| E.MUL.ADD.F.32.Z | Ensemble multiply add floating-point single zero |
| E.MUL.ADD.F.64 | Ensemble multiply add floating-point double |
| E.MUL.ADD.F.64.C | Ensemble multiply add floating-point double ceiling |
| E.MUL.ADD.F.64.F | Ensemble multiply add floating-point double floor |
| E.MUL.ADD.F.64.N | Ensemble multiply add floating-point double nearest |
| E.MUL.ADD.F.64.X | Ensemble multiply add floating-point double exact |
| E.MUL.ADD.F.64.Z | Ensemble multiply add floating-point double zero |
| E.MUL.ADD.F.128 | Ensemble multiply add floating-point quad |
| E.MUL.ADD.F.128.C | Ensemble multiply add floating-point quad ceiling |
| E.MUL.ADD.F.128.F | Ensemble multiply add floating-point quad floor |
| E.MUL.ADD.F.128.N | Ensemble multiply add floating-point quad nearest |
| E.MUL.ADD.F.128.X | Ensemble multiply add floating-point quad exact |
| E.MUL.ADD.F.128.Z | Ensemble multiply add floating-point quad zero |
| E.MUL.SUB.C.F.16 | Ensemble multiply subtract complex floating-point half |
| E.MUL.SUB.C.F.32 | Ensemble multiply subtract complex floating-point single |
| E.MUL.SUB.C.F.64 | Ensemble multiply subtract complex floating-point double |
| E.MUL.SUB.F.16 | Ensemble multiply subtract floating-point half |
| E.MUL.SUB.F.32 | Ensemble multiply subtract floating-point single |
| E.MUL.SUB.F.64 | Ensemble multiply subtract floating-point double |
| E.MUL.SUB.F.128 | Ensemble multiply subtract floating-point quad |

Fig. 38D

Selection

| class | op | type | prec | round/trap |
|-------------------|---------------|------|--------------|----------------|
| multiply add | E.MUL.AD D | F | 16 32 64 128 | NONE C F N X Z |
| | | C.F | 16 32 64 | NONE |
| multiply subtract | E.MUL.SU B | F | 16 32 64 128 | NONE |
| | | C.F | 16 32 64 | NONE |

Format

E.op.size rd@rc,rb

rd=eopsize(rd,rc,rb)




Fig. 38E

D finition

```
def mul(size,v,i,w,j) as
    mul ← fmul(F(size,vsize-1+i..i),F(size,wsize-1+j..j))
enddef

def EnsembleInplaceFloatingPoint(op,size,rd,rc,rb) as
    d ← RegRead(rd, 128)
    c ← RegRead(rc, 128)
    b ← RegRead(rb, 128)
    for i ← 0 to 128-size by size
        di ← F(prec,di+prec-1..i)
        case op of
            E.MUL.ADD.F:
                ai ← fadd(di, mul(prec,c,i,b,i))
            E.MUL.ADD.C.F:
                if (i and prec) then
                    ai ← fadd(di, fadd(mul(prec,c,i,b,i-prec), mul(c,i-prec,b,i)))
                else
                    ai ← fadd(di, fsub(mul(prec,c,i,b,i), mul(prec,c,i+prec,b,i+prec)))
                endif
            E.MUL.SUB.F:
                ai ← frsub(di, mul(prec,c,i,b,i))
            E.MUL.SUB.C.F:
                if (i and prec) then
                    ai ← frsub(di, fadd(mul(prec,c,i,b,i-prec), mul(c,i-prec,b,i)))
                else
                    ai ← frsub(di, fsub(mul(prec,c,i,b,i), mul(prec,c,i+prec,b,i+prec)))
                endif
            endif
        endcase
        ai+prec-1..i ← PackF(prec, ai, round)
    endfor
    RegWrite(rd, 128, a)
enddef
```

Exceptions

none

Fig. 38F

Operation codes

| | |
|-----------------|--|
| E.SCAL.ADD.F.16 | Ensemble scale add floating-point half |
| E.SCAL.ADD.F.32 | Ensemble scale add floating-point single |
| E.SCAL.ADD.F.64 | Ensemble scale add floating-point double |

Fig. 38G

Selection

| | | | | |
|-----------|--------------|------|----|----|
| class | op | prec | | |
| scale add | E.SCAL.ADD.F | 16 | 32 | 64 |

Format

E.SCAL.ADD.F.size ra=rd,rc,rb

ra=escaladdfsiz(rd,rc,rb)




Fig. 38H

Definition

```
def EnsembleFloatingPointTernary(op,prec,rd,rc,rb,ra) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  for i ← 0 to 128-prec by prec
    di ← F(prec,di+prec-1..i)
    ci ← F(prec,ci+prec-1..i)
    ai ← fadd(fmul(di, F(prec,bprec-1..0)), fmul(ci, F(prec,b2*prec-1..prec)))
    ai+prec-1..i ← PackF(prec, ai, none)
  endfor
  RegWrite(ra, 128, a)
enddef
```

Exceptions

none

Fig. 38I

| | |
|---------------|---|
| E.SUB.F.16 | Ensemble subtract floating-point half |
| E.SUB.F.16.C | Ensemble subtract floating-point half ceiling |
| E.SUB.F.16.F | Ensemble subtract floating-point half floor |
| E.SUB.F.16.N | Ensemble subtract floating-point half nearest |
| E.SUB.F.16.Z | Ensemble subtract floating-point half zero |
| E.SUB.F.16.X | Ensemble subtract floating-point half exact |
| E.SUB.F.32 | Ensemble subtract floating-point single |
| E.SUB.F.32.C | Ensemble subtract floating-point single ceiling |
| E.SUB.F.32.F | Ensemble subtract floating-point single floor |
| E.SUB.F.32.N | Ensemble subtract floating-point single nearest |
| E.SUB.F.32.Z | Ensemble subtract floating-point single zero |
| E.SUB.F.32.X | Ensemble subtract floating-point single exact |
| E.SUB.F.64 | Ensemble subtract floating-point double |
| E.SUB.F.64.C | Ensemble subtract floating-point double ceiling |
| E.SUB.F.64.F | Ensemble subtract floating-point double floor |
| E.SUB.F.64.N | Ensemble subtract floating-point double nearest |
| E.SUB.F.64.Z | Ensemble subtract floating-point double zero |
| E.SUB.F.64.X | Ensemble subtract floating-point double exact |
| E.SUB.F.128 | Ensemble subtract floating-point quad |
| E.SUB.F.128.C | Ensemble subtract floating-point quad ceiling |
| E.SUB.F.128.F | Ensemble subtract floating-point quad floor |
| E.SUB.F.128.N | Ensemble subtract floating-point quad nearest |
| E.SUB.F.128.Z | Ensemble subtract floating-point quad zero |
| E.SUB.F.128.X | Ensemble subtract floating-point quad exact |

Fig. 39A

Selection

| class | op | prec | round/trap |
|----------|----------------------|--------------|----------------|
| set | SET. E LG L GE | 16 32 64 128 | NONE X |
| subtract | SUB | 16 32 64 128 | NONE C F N X Z |

Format

E.op.prec.round rd=rb,rc

rd=eopprecround(rb,rc)




Fig. 39B

Definition

```
def EnsembleReversedFloatingPoint(op,prec,round,rd,rc,rb) as
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  for i ← 0 to 128-prec by prec
    ci ← F(prec,ci+prec-1..i)
    bi ← F(prec,bi+prec-1..i)
    ai ← frsubr(ci,-bi, round)
    ai+prec-1..i ← PackF(prec, ai, round)
  endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Floating-point arithmetic

Fig. 39C

Operation codes

| | |
|------------------|---|
| G.SET.E.F.16 | Group set equal floating-point half |
| G.SET.E.F.16.X | Group set equal floating-point half exact |
| G.SET.E.F.32 | Group set equal floating-point single |
| G.SET.E.F.32.X | Group set equal floating-point single exact |
| G.SET.E.F.64 | Group set equal floating-point double |
| G.SET.E.F.64.X | Group set equal floating-point double exact |
| G.SET.E.F.128 | Group set equal floating-point quad |
| G.SET.E.F.128.X | Group set equal floating-point quad exact |
| G.SET.GE.F.16.X | Group set greater equal floating-point half exact |
| G.SET.GE.F.32.X | Group set greater equal floating-point single exact |
| G.SET.GE.F.64.X | Group set greater equal floating-point double exact |
| G.SET.GE.F.128.X | Group set greater equal floating-point quad exact |
| G.SET.LG.F.16 | Group set less greater floating-point half |
| G.SET.LG.F.16.X | Group set less greater floating-point half exact |
| G.SET.LG.F.32 | Group set less greater floating-point single |
| G.SET.LG.F.32.X | Group set less greater floating-point single exact |
| G.SET.LG.F.64 | Group set less greater floating-point double |
| G.SET.LG.F.64.X | Group set less greater floating-point double exact |
| G.SET.LG.F.128 | Group set less greater floating-point quad |
| G.SET.LG.F.128.X | Group set less greater floating-point quad exact |
| G.SET.L.F.16 | Group set less floating-point half |
| G.SET.L.F.16.X | Group set less floating-point half exact |
| G.SET.L.F.32 | Group set less floating-point single |
| G.SET.L.F.32.X | Group set less floating-point single exact |
| G.SET.L.F.64 | Group set less floating-point double |
| G.SET.L.F.64.X | Group set less floating-point double exact |
| G.SET.L.F.128 | Group set less floating-point quad |
| G.SET.L.F.128.X | Group set less floating-point quad exact |
| G.SET.GE.F.16 | Group set greater equal floating-point half |
| G.SET.GE.F.32 | Group set greater equal floating-point single |
| G.SET.GE.F.64 | Group set greater equal floating-point double |
| G.SET.GE.F.128 | Group set greater equal floating-point quad |

Fig. 39D

Equivalencies

| | |
|-------------------------|--|
| <i>G.SET.LE.F.16.X</i> | Group set less equal floating-point half exact |
| <i>G.SET.LE.F.32.X</i> | Group set less equal floating-point single exact |
| <i>G.SET.LE.F.64.X</i> | Group set less equal floating-point double exact |
| <i>G.SET.LE.F.128.X</i> | Group set less equal floating-point quad exact |
| <i>G.SET.G.F.16</i> | Group set greater floating-point half |
| <i>G.SET.G.F.16.X</i> | Group set greater floating-point half exact |
| <i>G.SET.G.F.32</i> | Group set greater floating-point single |
| <i>G.SET.G.F.32.X</i> | Group set greater floating-point single exact |
| <i>G.SET.G.F.64</i> | Group set greater floating-point double |
| <i>G.SET.G.F.64.X</i> | Group set greater floating-point double exact |
| <i>G.SET.G.F.128</i> | Group set greater floating-point quad |
| <i>G.SET.G.F.128.X</i> | Group set greater floating-point quad exact |
| <i>G.SET.LE.F.16</i> | Group set less equal floating-point half |
| <i>G.SET.LE.F.32</i> | Group set less equal floating-point single |
| <i>G.SET.LE.F.64</i> | Group set less equal floating-point double |
| <i>G.SET.LE.F.128</i> | Group set less equal floating-point quad |

| | | |
|-----------------------------------|---|-----------------------------------|
| <i>G.SET.G.F.prec rd=rb,rc</i> | → | <i>G.SET.L.F.prec rd=rc,rb</i> |
| <i>G.SET.G.F.prec.X rd=rb,rc</i> | → | <i>G.SET.L.F.prec.X rd=rc,rb</i> |
| <i>G.SET.LE.F.prec rd=rb,rc</i> | → | <i>G.SET.GE.F.prec rd=rc,rb</i> |
| <i>G.SET.LE.F.prec.X rd=rb,rc</i> | → | <i>G.SET.GE.F.prec.X rd=rc,rb</i> |

Fig. 39E

Selection

| class | op | prec | round/trap |
|-------|---------------------------------------|--------------------|------------|
| set | SET. E LG L GE G LE | 16 32 64 128 | NONE X |

Format

G.op.prec.round rd=rb,rc

rc=gopprecround(rb,ra)




Fig 39F

Definition

```
def GroupFloatingPointReversed(op,prec,round,rd,rc,rb) as
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  for i ← 0 to 128-prec by prec
    ci ← F(prec,ci+prec-1..i)
    bi ← F(prec,bi+prec-1..i)
    if round≠NONE then
      if (di.t = SNAN) or (ci.t = SNAN) then
        raise FloatingPointArithmetic
      endif
      case op of
        G.SET.L.F, G.SET.GE.F:
          if (di.t = QNAN) or (ci.t = QNAN) then
            raise FloatingPointArithmetic
          endif
        others: //nothing
      endcase
    endif
    case op of
      G.SET.L.F:
        ai ← bi?≥ci
      G.SET.GE.F:
        ai ← bi!?<ci
      G.SET.E.F:
        ai ← bi=ci
      G.SET.LG.F:
        ai ← bi≠ci
    endcase
    ai+prec-1..i ← aiprec
  endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Floating-point arithmetic

Fig. 39G

| | |
|------------------|--|
| G.COM.E.F.16 | Group compare equal floating-point half |
| G.COM.E.F.16.X | Group compare equal floating-point half exact |
| G.COM.E.F.32 | Group compare equal floating-point single |
| G.COM.E.F.32.X | Group compare equal floating-point single exact |
| G.COM.E.F.64 | Group compare equal floating-point double |
| G.COM.E.F.64.X | Group compare equal floating-point double exact |
| G.COM.E.F.128 | Group compare equal floating-point quad |
| G.COM.E.F.128.X | Group compare equal floating-point quad exact |
| G.COM.GE.F.16 | Group compare greater or equal floating-point half |
| G.COM.GE.F.16.X | Group compare greater or equal floating-point half exact |
| G.COM.GE.F.32 | Group compare greater or equal floating-point single |
| G.COM.GE.F.32.X | Group compare greater or equal floating-point single exact |
| G.COM.GE.F.64 | Group compare greater or equal floating-point double |
| G.COM.GE.F.64.X | Group compare greater or equal floating-point double exact |
| G.COM.GE.F.128 | Group compare greater or equal floating-point quad |
| G.COM.GE.F.128.X | Group compare greater or equal floating-point quad exact |
| G.COM.L.F.16 | Group compare less floating-point half |
| G.COM.L.F.16.X | Group compare less floating-point half exact |
| G.COM.L.F.32 | Group compare less floating-point single |
| G.COM.L.F.32.X | Group compare less floating-point single exact |
| G.COM.L.F.64 | Group compare less floating-point double |
| G.COM.L.F.64.X | Group compare less floating-point double exact |
| G.COM.L.F.128 | Group compare less floating-point quad |
| G.COM.L.F.128.X | Group compare less floating-point quad exact |
| G.COM.LG.F.16 | Group compare less or greater floating-point half |
| G.COM.LG.F.16.X | Group compare less or greater floating-point half exact |
| G.COM.LG.F.32 | Group compare less or greater floating-point single |
| G.COM.LG.F.32.X | Group compare less or greater floating-point single exact |
| G.COM.LG.F.64 | Group compare less or greater floating-point double |
| G.COM.LG.F.64.X | Group compare less or greater floating-point double exact |
| G.COM.LG.F.128 | Group compare less or greater floating-point quad |
| G.COM.LG.F.128.X | Group compare less or greater floating-point quad exact |

Fig. 40A

Format

G.COM.op.prec.round rd,rc

rc=gcomopprecround(rd,rc)




Fig. 40B

Definition

```
def GroupCompareFloatingPoint(op,prec,round,rd,rc) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  for i ← 0 to 128-prec by prec
    di ← F(prec,di+prec-1..i)
    ci ← F(prec,ci+prec-1..i)
    if round≠NONE then
      if (di.t = SNAN) or (ci.t = SNAN) then
        raise FloatingPointArithmetic
      endif
      case op of
        G.COM.L.F, G.COM.GE.F:
          if (di.t = QNAN) or (ci.t = QNAN) then
            raise FloatingPointArithmetic
          endif
        others: //nothing
      endcase
    endif
    case op of
      G.COM.L.F:
        ai ← di?≥ci
      G.COM.GE.F:
        ai ← di!?<ci
      G.COM.E.F:
        ai ← di=ci
      G.COM.LG.F:
        ai ← di≠ci
    endcase
    ai+prec-1..i ← ai
  endfor
  if (a ≠ 0) then
    raise FloatingPointArithmetic
  endif
enddef
```

Exceptions

Floating-point arithmetic

Fig. 40C

| | |
|-------------------|--|
| E.ABS.F.16 | Ensemble absolute value floating-point half |
| E.ABS.F.16.X | Ensemble absolute value floating-point half exception |
| E.ABS.F.32 | Ensemble absolute value floating-point single |
| E.ABS.F.32.X | Ensemble absolute value floating-point single exception |
| E.ABS.F.64 | Ensemble absolute value floating-point double |
| E.ABS.F.64.X | Ensemble absolute value floating-point double exception |
| E.ABS.F.128 | Ensemble absolute value floating-point quad |
| E.ABS.F.128.X | Ensemble absolute value floating-point quad exception |
| E.COPY.F.16 | Ensemble copy floating-point half |
| E.COPY.F.16.X | Ensemble copy floating-point half exception |
| E.COPY.F.32 | Ensemble copy floating-point single |
| E.COPY.F.32.X | Ensemble copy floating-point single exception |
| E.COPY.F.64 | Ensemble copy floating-point double |
| E.COPY.F.64.X | Ensemble copy floating-point double exception |
| E.COPY.F.128 | Ensemble copy floating-point quad |
| E.COPY.F.128.X | Ensemble copy floating-point quad exception |
| E.DEFLATE.F.32 | Ensemble convert floating-point half from single |
| E.DEFLATE.F.32.C | Ensemble convert floating-point half from single ceiling |
| E.DEFLATE.F.32.F | Ensemble convert floating-point half from single floor |
| E.DEFLATE.F.32.N | Ensemble convert floating-point half from single nearest |
| E.DEFLATE.F.32.X | Ensemble convert floating-point half from single exact |
| E.DEFLATE.F.32.Z | Ensemble convert floating-point half from single zero |
| E.DEFLATE.F.64 | Ensemble convert floating-point single from double |
| E.DEFLATE.F.64.C | Ensemble convert floating-point single from double ceiling |
| E.DEFLATE.F.64.F | Ensemble convert floating-point single from double floor |
| E.DEFLATE.F.64.N | Ensemble convert floating-point single from double nearest |
| E.DEFLATE.F.64.X | Ensemble convert floating-point single from double exact |
| E.DEFLATE.F.64.Z | Ensemble convert floating-point single from double zero |
| E.DEFLATE.F.128 | Ensemble convert floating-point double from quad |
| E.DEFLATE.F.128.C | Ensemble convert floating-point double from quad ceiling |
| E.DEFLATE.F.128.F | Ensemble convert floating-point double from quad floor |
| E.DEFLATE.F.128.N | Ensemble convert floating-point double from quad nearest |
| E.DEFLATE.F.128.X | Ensemble convert floating-point double from quad exact |
| E.DEFLATE.F.128.Z | Ensemble convert floating-point double from quad zero |
| E.FLOAT.F.16 | Ensemble convert floating-point half from doublets |
| E.FLOAT.F.16.C | Ensemble convert floating-point half from doublets ceiling |
| E.FLOAT.F.16.F | Ensemble convert floating-point half from doublets floor |
| E.FLOAT.F.16.N | Ensemble convert floating-point half from doublets nearest |
| E.FLOAT.F.16.X | Ensemble convert floating-point half from doublets exact |
| E.FLOAT.F.16.Z | Ensemble convert floating-point half from doublets zero |

Fig. 41A

| | |
|------------------|--|
| E.FLOAT.F.32 | Ensemble convert floating-point single from quadlets |
| E.FLOAT.F.32.C | Ensemble convert floating-point single from quadlets ceiling |
| E.FLOAT.F.32.F | Ensemble convert floating-point single from quadlets floor |
| E.FLOAT.F.32.N | Ensemble convert floating-point single from quadlets nearest |
| E.FLOAT.F.32.X | Ensemble convert floating-point single from quadlets exact |
| E.FLOAT.F.32.Z | Ensemble convert floating-point single from quadlets zero |
| E.FLOAT.F.64 | Ensemble convert floating-point double from octlets |
| E.FLOAT.F.64.C | Ensemble convert floating-point double from octlets ceiling |
| E.FLOAT.F.64.F | Ensemble convert floating-point double from octlets floor |
| E.FLOAT.F.64.N | Ensemble convert floating-point double from octlets nearest |
| E.FLOAT.F.64.X | Ensemble convert floating-point double from octlets exact |
| E.FLOAT.F.64.Z | Ensemble convert floating-point double from octlets zero |
| E.FLOAT.F.128 | Ensemble convert floating-point quad from hexlet |
| E.FLOAT.F.128.C | Ensemble convert floating-point quad from hexlet ceiling |
| E.FLOAT.F.128.F | Ensemble convert floating-point quad from hexlet floor |
| E.FLOAT.F.128.N | Ensemble convert floating-point quad from hexlet nearest |
| E.FLOAT.F.128.X | Ensemble convert floating-point quad from hexlet exact |
| E.FLOAT.F.128.Z | Ensemble convert floating-point quad from hexlet zero |
| E.INFLATE.F.16 | Ensemble convert floating-point single from half |
| E.INFLATE.F.16.X | Ensemble convert floating-point single from half exception |
| E.INFLATE.F.32 | Ensemble convert floating-point double from single |
| E.INFLATE.F.32.X | Ensemble convert floating-point double from single exception |
| E.INFLATE.F.64 | Ensemble convert floating-point quad from double |
| E.INFLATE.F.64.X | Ensemble convert floating-point quad from double exception |
| E.NEG.F.16 | Ensemble negate floating-point half |
| E.NEG.F.16.X | Ensemble negate floating-point half exception |
| E.NEG.F.32 | Ensemble negate floating-point single |
| E.NEG.F.32.X | Ensemble negate floating-point single exception |
| E.NEG.F.64 | Ensemble negate floating-point double |
| E.NEG.F.64.X | Ensemble negate floating-point double exception |
| E.NEG.F.128 | Ensemble negate floating-point quad |
| E.NEG.F.128.X | Ensemble negate floating-point quad exception |
| E.RECEST.F.16 | Ensemble reciprocal estimate floating-point half |
| E.RECEST.F.16.X | Ensemble reciprocal estimate floating-point half exception |
| E.RECEST.F.32 | Ensemble reciprocal estimate floating-point single |
| E.RECEST.F.32.X | Ensemble reciprocal estimate floating-point single exception |
| E.RECEST.F.64 | Ensemble reciprocal estimate floating-point double |
| E.RECEST.F.64.X | Ensemble reciprocal estimate floating-point double exception |
| E.RECEST.F.128 | Ensemble reciprocal estimate floating-point quad |
| E.RECEST.F.128.X | Ensemble reciprocal estimate floating-point quad exception |

Fig. 41A (cont'd)

| | |
|-------------------|--|
| E.RSQREST.F.16 | Ensemble floating-point reciprocal square root estimate half |
| E.RSQREST.F.16.X | Ensemble floating-point reciprocal square root estimate half exact |
| E.RSQREST.F.32 | Ensemble floating-point reciprocal square root estimate single |
| E.RSQREST.F.32.X | Ensemble floating-point reciprocal square root estimate single exact |
| E.RSQREST.F.64 | Ensemble floating-point reciprocal square root estimate double |
| E.RSQREST.F.64.X | Ensemble floating-point reciprocal square root estimate double exact |
| E.RSQREST.F.128 | Ensemble floating-point reciprocal square root estimate quad |
| E.RSQREST.F.128.X | Ensemble floating-point reciprocal square root estimate quad exact |
| E.SINK.F.16 | Ensemble convert floating-point doublets from half nearest default |
| E.SINK.F.16.C | Ensemble convert floating-point doublets from half ceiling |
| E.SINK.F.16.C.D | Ensemble convert floating-point doublets from half ceiling default |
| E.SINK.F.16.F | Ensemble convert floating-point doublets from half floor |
| E.SINK.F.16.F.D | Ensemble convert floating-point doublets from half floor default |
| E.SINK.F.16.N | Ensemble convert floating-point doublets from half nearest |
| E.SINK.F.16.X | Ensemble convert floating-point doublets from half exact |
| E.SINK.F.16.Z | Ensemble convert floating-point doublets from half zero |
| E.SINK.F.16.Z.D | Ensemble convert floating-point doublets from half zero default |
| E.SINK.F.32 | Ensemble convert floating-point quadlets from single nearest default |
| E.SINK.F.32.C | Ensemble convert floating-point quadlets from single ceiling |
| E.SINK.F.32.C.D | Ensemble convert floating-point quadlets from single ceiling default |
| E.SINK.F.32.F | Ensemble convert floating-point quadlets from single floor |
| E.SINK.F.32.F.D | Ensemble convert floating-point quadlets from single floor default |
| E.SINK.F.32.N | Ensemble convert floating-point quadlets from single nearest |
| E.SINK.F.32.X | Ensemble convert floating-point quadlets from single exact |
| E.SINK.F.32.Z | Ensemble convert floating-point quadlets from single zero |
| E.SINK.F.32.Z.D | Ensemble convert floating-point quadlets from single zero default |
| E.SINK.F.64 | Ensemble convert floating-point octlets from double nearest default |
| E.SINK.F.64.C | Ensemble convert floating-point octlets from double ceiling |
| E.SINK.F.64.C.D | Ensemble convert floating-point octlets from double ceiling default |
| E.SINK.F.64.F | Ensemble convert floating-point octlets from double floor |
| E.SINK.F.64.F.D | Ensemble convert floating-point octlets from double floor default |
| E.SINK.F.64.N | Ensemble convert floating-point octlets from double nearest |
| E.SINK.F.64.X | Ensemble convert floating-point octlets from double exact |
| E.SINK.F.64.Z | Ensemble convert floating-point octlets from double zero |
| E.SINK.F.64.Z.D | Ensemble convert floating-point octlets from double zero default |
| E.SINK.F.128 | Ensemble convert floating-point hexlet from quad nearest default |
| E.SINK.F.128.C | Ensemble convert floating-point hexlet from quad ceiling |
| E.SINK.F.128.C.D | Ensemble convert floating-point hexlet from quad ceiling default |
| E.SINK.F.128.F | Ensemble convert floating-point hexlet from quad floor |
| E.SINK.F.128.F.D | Ensemble convert floating-point hexlet from quad floor default |

Fig. 41A (cont'd)

| | |
|------------------|---|
| E.SINK.F.128.N | Ensemble convert floating-point hexlet from quad nearest |
| E.SINK.F.128.X | Ensemble convert floating-point hexlet from quad exact |
| E.SINK.F.128.Z | Ensemble convert floating-point hexlet from quad zero |
| E.SINK.F.128.Z.D | Ensemble convert floating-point hexlet from quad zero default |
| E.SQR.F.16 | Ensemble square root floating-point half |
| E.SQR.F.16.C | Ensemble square root floating-point half ceiling |
| E.SQR.F.16.F | Ensemble square root floating-point half floor |
| E.SQR.F.16.N | Ensemble square root floating-point half nearest |
| E.SQR.F.16.X | Ensemble square root floating-point half exact |
| E.SQR.F.16.Z | Ensemble square root floating-point half zero |
| E.SQR.F.32 | Ensemble square root floating-point single |
| E.SQR.F.32.C | Ensemble square root floating-point single ceiling |
| E.SQR.F.32.F | Ensemble square root floating-point single floor |
| E.SQR.F.32.N | Ensemble square root floating-point single nearest |
| E.SQR.F.32.X | Ensemble square root floating-point single exact |
| E.SQR.F.32.Z | Ensemble square root floating-point single zero |
| E.SQR.F.64 | Ensemble square root floating-point double |
| E.SQR.F.64.C | Ensemble square root floating-point double ceiling |
| E.SQR.F.64.F | Ensemble square root floating-point double floor |
| E.SQR.F.64.N | Ensemble square root floating-point double nearest |
| E.SQR.F.64.X | Ensemble square root floating-point double exact |
| E.SQR.F.64.Z | Ensemble square root floating-point double zero |
| E.SQR.F.128 | Ensemble square root floating-point quad |
| E.SQR.F.128.C | Ensemble square root floating-point quad ceiling |
| E.SQR.F.128.F | Ensemble square root floating-point quad floor |
| E.SQR.F.128.N | Ensemble square root floating-point quad nearest |
| E.SQR.F.128.X | Ensemble square root floating-point quad exact |
| E.SQR.F.128.Z | Ensemble square root floating-point quad zero |
| E.SUM.F.16 | Ensemble sum floating-point half |
| E.SUM.F.16.C | Ensemble sum floating-point half ceiling |
| E.SUM.F.16.F | Ensemble sum floating-point half floor |
| E.SUM.F.16.N | Ensemble sum floating-point half nearest |
| E.SUM.F.16.X | Ensemble sum floating-point half exact |
| E.SUM.F.16.Z | Ensemble sum floating-point half zero |
| E.SUM.F.32 | Ensemble sum floating-point single |
| E.SUM.F.32.C | Ensemble sum floating-point single ceiling |
| E.SUM.F.32.F | Ensemble sum floating-point single floor |
| E.SUM.F.32.N | Ensemble sum floating-point single nearest |
| E.SUM.F.32.X | Ensemble sum floating-point single exact |
| E.SUM.F.32.Z | Ensemble sum floating-point single zero |

Fig. 41A (cont'd)

| | |
|---------------|--|
| E.SUM.F.64 | Ensemble sum floating-point doubl |
| E.SUM.F.64.C | Ensemble sum floating-point double ceiling |
| E.SUM.F.64.F | Ensemble sum floating-point double floor |
| E.SUM.F.64.N | Ensemble sum floating-point double nearest |
| E.SUM.F.64.X | Ensemble sum floating-point double exact |
| E.SUM.F.64.Z | Ensemble sum floating-point double zero |
| E.SUM.F.128 | Ensemble sum floating-point quad |
| E.SUM.F.128.C | Ensemble sum floating-point quad ceiling |
| E.SUM.F.128.F | Ensemble sum floating-point quad floor |
| E.SUM.F.128.N | Ensemble sum floating-point quad nearest |
| E.SUM.F.128.X | Ensemble sum floating-point quad exact |
| E.SUM.F.128.Z | Ensemble sum floating-point quad zero |

Selection

| | op | prec | round/trap |
|---------------------------------|---------|--------------|-------------------------------|
| copy | COPY | 16 32 64 128 | NONE X |
| absolute value | ABS | 16 32 64 128 | NONE X |
| float from integer | FLOAT | 16 32 64 128 | NONE C F N X Z |
| integer from float | SINK | 16 32 64 128 | NONE C F N X Z C.D F.D Z.D |
| increase format precision | INFLATE | 16 32 64 | NONE X |
| decrease format precision | DEFLATE | 32 64 128 | NONE C F N X Z |
| negate | NEG | 16 32 64 128 | NONE X |
| reciprocal estimate | RECEST | 16 32 64 128 | NONE X |
| reciprocal square root estimate | RSQREST | 16 32 64 128 | NONE X |
| square root | SQR | 16 32 64 128 | NONE C F N X Z |
| sum | SUM | 16 32 64 128 | NONE C F N X Z |

Fig. 41A (cont'd)

Format

E.op.prec.round rd=rc

rd=eopprecround(rc)




Fig. 41B

Definition

```
def EnsembleUnaryFloatingPoint(op,prec,round,rd,rc) as
  c ← RegRead(rc, 128)
  case op of
    E.ABS.F, E.NEG.F, E.SQR.F:
      for i ← 0 to 128-prec by prec
        ci ← F(prec,ci+prec-1..i)
        case op of
          E.ABS.F:
            ai.t ← ci.t
            ai.s ← 0
            ai.e ← ci.e
            ai.f ← ci.f
          E.COPY.F:
            ai ← ci
          E.NEG.F:
            ai.t ← ci.t
            ai.s ← ~ci.s
            ai.e ← ci.e
            ai.f ← ci.f
          E.RECEST.F:
            ai ← frecest(ci)
          E.RSQREST.F:
            ai ← frsqrest(ci)
          E.SQR.F:
            ai ← fsqr(ci)
        endcase
        ai+prec-1..i ← PackF(prec, ai, round)
      endfor
    E.SUM.F:
      p[0].t ← NULL
      for i ← 0 to 128-prec by prec
        p[i+prec] ← fadd(p[i], F(prec,ci+prec-1..i))
      endfor
      a ← PackF(prec, p[128], round)
    E.SINK.F:
      for i ← 0 to 128-prec by prec
        ci ← F(prec,ci+prec-1..i)
        ai+prec-1..i ← fsinkr(prec, ci, round)
      endfor
    E.FLOAT.F:
      for i ← 0 to 128-prec by prec
        ci.t ← NORM
        ci.e ← 0
        ci.s ← ci+prec-1
        ci.f ← ci.s ? 1+~ci+prec-2..i : ci+prec-2..i
        ai+prec-1..i ← PackF(prec, ci, round)
      endfor
```

Fig. 41C


```

E.INFLATE.F:
  for i ← 0 to 64-prec by prec
    ci ← F(prec, ci+prec-1..i)
    ai+i+prec+prec-1..i ← PackF(prec+prec, ci, round)
  endfor
E.DEFLATE.F:
  for i ← 0 to 128-prec by prec
    ci ← F(prec, ci+prec-1..i)
    ai/2+prec/2-1..i/2 ← PackF(prec/2, ci, round)
  endfor
  a127..64 ← 0
endcase
RegWrite[rd, 128, a]
enddef

```

Exceptions

Floating-point arithmetic

Fig. 41C (cont'd)

| | |
|------------|---------------------------------------|
| E.MUL.G.8 | Ensemble multiply Galois field byte |
| E.MUL.G.64 | Ensemble multiply Galois field octlet |

Fig. 42A

Format

E.MUL.G.size ra=rd,rc,rb

ra=emulgsiz(rd,rc,rb)




Fig.42B

Definition

```
def c ← PolyMultiply(size,a,b) as
  p[0] ← 02*size
  for k ← 0 to size-1
    p[k+1] ← p[k] ^ ak ? (0size-k || b || 0k) : 02*size
  endfor
  c ← p[size]
enddef

def c ← PolyResidue(size,a,b) as
  p[0] ← a
  for k ← size-1 to 0 by -1
    p[k+1] ← p[k] p[0]size+k ? (0size-k || 11 || b || 0k) : 02*size
  endfor
  c ← p[size]size-1..0
enddef

def EnsembleTernary(op,size,rd,rc,rb,ra) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  case op of
    E.MUL.G:
      for i ← 0 to 128-size by size
        asize-1+i..i ← PolyResidue(size,PolyMul(size,csize-1+i..i,bsize-1+i..i),dsize-1+i..i)
      endfor
  endcase
  RegWrite(ra, 128, a)
enddef
```

Exceptions

none

Fig. 42C




Fig. 42D

| | |
|------------------|-------------------------------------|
| X.COMPRESS.2 | Crossbar compress signed pecks |
| X.COMPRESS.4 | Crossbar compress signed nibbles |
| X.COMPRESS.8 | Crossbar compress signed bytes |
| X.COMPRESS.16 | Crossbar compress signed doublets |
| X.COMPRESS.32 | Crossbar compress signed quadlets |
| X.COMPRESS.64 | Crossbar compress signed octlets |
| X.COMPRESS.128 | Crossbar compress signed hexlet |
| X.COMPRESS.U.2 | Crossbar compress unsigned pecks |
| X.COMPRESS.U.4 | Crossbar compress unsigned nibbles |
| X.COMPRESS.U.8 | Crossbar compress unsigned bytes |
| X.COMPRESS.U.16 | Crossbar compress unsigned doublets |
| X.COMPRESS.U.32 | Crossbar compress unsigned quadlets |
| X.COMPRESS.U.64 | Crossbar compress unsigned octlets |
| X.COMPRESS.U.128 | Crossbar compress unsigned hexlet |
| X.EXPAND.2 | Crossbar expand signed pecks |
| X.EXPAND.4 | Crossbar expand signed nibbles |
| X.EXPAND.8 | Crossbar expand signed bytes |
| X.EXPAND.16 | Crossbar expand signed doublets |
| X.EXPAND.32 | Crossbar expand signed quadlets |
| X.EXPAND.64 | Crossbar expand signed octlets |
| X.EXPAND.128 | Crossbar expand signed hexlet |
| X.EXPAND.U.2 | Crossbar expand unsigned pecks |
| X.EXPAND.U.4 | Crossbar expand unsigned nibbles |
| X.EXPAND.U.8 | Crossbar expand unsigned bytes |
| X.EXPAND.U.16 | Crossbar expand unsigned doublets |
| X.EXPAND.U.32 | Crossbar expand unsigned quadlets |
| X.EXPAND.U.64 | Crossbar expand unsigned octlets |
| X.EXPAND.U.128 | Crossbar expand unsigned hexlet |
| X.ROTL.2 | Crossbar rotate left pecks |
| X.ROTL.4 | Crossbar rotate left nibbles |
| X.ROTL.8 | Crossbar rotate left bytes |
| X.ROTL.16 | Crossbar rotate left doublets |
| X.ROTL.32 | Crossbar rotate left quadlets |
| X.ROTL.64 | Crossbar rotate left octlets |
| X.ROTL.128 | Crossbar rotate left hexlet |
| X.ROTR.2 | Crossbar rotate right pecks |
| X.ROTR.4 | Crossbar rotate right nibbles |
| X.ROTR.8 | Crossbar rotate right bytes |
| X.ROTR.16 | Crossbar rotate right doublets |

Fig. 43A

| | |
|---------------|--|
| X.ROTR.32 | Crossbar rotate right quadlets |
| X.ROTR.64 | Crossbar rotate right octlets |
| X.ROTR.128 | Crossbar rotate right hexlet |
| X.SHL.2 | Crossbar shift left pecks |
| X.SHL.2.O | Crossbar shift left signed pecks check overflow |
| X.SHL.4 | Crossbar shift left nibbles |
| X.SHL.4.O | Crossbar shift left signed nibbles check overflow |
| X.SHL.8 | Crossbar shift left bytes |
| X.SHL.8.O | Crossbar shift left signed bytes check overflow |
| X.SHL.16 | Crossbar shift left doublets |
| X.SHL.16.O | Crossbar shift left signed doublets check overflow |
| X.SHL.32 | Crossbar shift left quadlets |
| X.SHL.32.O | Crossbar shift left signed quadlets check overflow |
| X.SHL.64 | Crossbar shift left octlets |
| X.SHL.64.O | Crossbar shift left signed octlets check overflow |
| X.SHL.128 | Crossbar shift left hexlet |
| X.SHL.128.O | Crossbar shift left signed hexlet check overflow |
| X.SHL.U.2.O | Crossbar shift left unsigned pecks check overflow |
| X.SHL.U.4.O | Crossbar shift left unsigned nibbles check overflow |
| X.SHL.U.8.O | Crossbar shift left unsigned bytes check overflow |
| X.SHL.U.16.O | Crossbar shift left unsigned doublets check overflow |
| X.SHL.U.32.O | Crossbar shift left unsigned quadlets check overflow |
| X.SHL.U.64.O | Crossbar shift left unsigned octlets check overflow |
| X.SHL.U.128.O | Crossbar shift left unsigned hexlet check overflow |
| X.SHR.2 | Crossbar signed shift right pecks |
| X.SHR.4 | Crossbar signed shift right nibbles |
| X.SHR.8 | Crossbar signed shift right bytes |
| X.SHR.16 | Crossbar signed shift right doublets |
| X.SHR.32 | Crossbar signed shift right quadlets |
| X.SHR.64 | Crossbar signed shift right octlets |
| X.SHR.128 | Crossbar signed shift right hexlet |
| X.SHR.U.2 | Crossbar shift right unsigned pecks |
| X.SHR.U.4 | Crossbar shift right unsigned nibbles |
| X.SHR.U.8 | Crossbar shift right unsigned bytes |
| X.SHR.U.16 | Crossbar shift right unsigned doublets |
| X.SHR.U.32 | Crossbar shift right unsigned quadlets |
| X.SHR.U.64 | Crossbar shift right unsigned octlets |
| X.SHR.U.128 | Crossbar shift right unsigned hexlet |

Fig. 43A (cont'd)


Selection

| class | op | size |
|-----------|----------|-----------|
| precision | EXPAND | EXPAND.U |
| | COMPRESS | COMPRESS. |
| | U | |
| shift | ROTR | ROTL |
| | SHR | SHL |
| | SHL.O | SHL.U.O |
| | SHR.U | |

Format

X.op.size rd=rc,rb

rd=xopsize(rc,rb)



lsize $\leftarrow \log(\text{size})$

s $\leftarrow \text{lsize}_2$

sz $\leftarrow \text{lsize}_{1..0}$

Fig. 43B

Definition

```

def Crossbar(op,size,rd,rc,rb)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  shift ← b and (size-1)
  case op5..2 || 02 of
    X.COMPRESS:
      hsize ← size/2
      for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
          ai+hsize-1..i ← Ci+i+shift+hsize-1..i+i+shift
        else
          ai+hsize-1..i ← Ci+i+size-1shift-hsize || Ci+i+size-1..i+i+shift
        endif
      endfor
      a127..64 ← 0
    X.COMPRESS.U:
      hsize ← size/2
      for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
          ai+hsize-1..i ← Ci+i+shift+hsize-1..i+i+shift
        else
          ai+hsize-1..i ← 0shift-hsize || Ci+i+size-1..i+i+shift
        endif
      endfor
      a127..64 ← 0
    X.EXPAND:
      hsize ← size/2
      for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
          ai+i+size-1..i+i ← Ci+hsize-1hsize-shift || Ci+hsize-1..i || 0shift
        else
          ai+i+size-1..i+i ← Ci+size-shift-1..i || 0shift
        endif
      endfor
    X.EXPAND.U:
      hsize ← size/2
      for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
          ai+i+size-1..i+i ← 0hsize-shift || Ci+hsize-1..i || 0shift
        else
          ai+i+size-1..i+i ← Ci+size-shift-1..i || 0shift
        endif
      endfor
    X.ROTL:
      for i ← 0 to 128-size by size
        ai+size-1..i ← Ci+size-1-shift..i || Ci+size-1..i+size-1-shift
      endfor

```

Fig. 43C


```

X.ROTR:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow c_{i+shift-1..i} \parallel c_{i+size-1..i+shift}$ 
  endfor
X.SHL:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow c_{i+size-1-shift..i} \parallel 0^{shift}$ 
  endfor
X.SHL.O:
  for i ← 0 to 128-size by size
    if  $c_{i+size-1..i+size-1-shift} \neq c_{i+size-1-shift}^{shift+1}$  then
      raise FixedPointArithmetic
    endif
     $a_{i+size-1..i} \leftarrow c_{i+size-1-shift..i} \parallel 0^{shift}$ 
  endfor
X.SHL.U.O:
  for i ← 0 to 128-size by size
    if  $c_{i+size-1..i+size-shift} \neq 0^{shift}$  then
      raise FixedPointArithmetic
    endif
     $a_{i+size-1..i} \leftarrow c_{i+size-1-shift..i} \parallel 0^{shift}$ 
  endfor
X.SHR:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow c_{i+size-1}^{shift} \parallel c_{i+size-1..i+shift}$ 
  endfor
X.SHR.U:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow 0^{shift} \parallel c_{i+size-1..i+shift}$ 
  endfor
endcase
RegWrite(rd, 128, a)
enddef

```

Exceptions

Fixed-point arithmetic

Fig. 43C (cont'd)




Fig. 43D

Operation codes


| | |
|-------------|-------------------------------------|
| X.SHL.M.2 | Crossbar shift left merge pecks |
| X.SHL.M.4 | Crossbar shift left merge nibbles |
| X.SHL.M.8 | Crossbar shift left merge bytes |
| X.SHL.M.16 | Crossbar shift left merge doublets |
| X.SHL.M.32 | Crossbar shift left merge quadlets |
| X.SHL.M.64 | Crossbar shift left merge octlets |
| X.SHL.M.128 | Crossbar shift left merge hexlet |
| X.SHR.M.2 | Crossbar shift right merge pecks |
| X.SHR.M.4 | Crossbar shift right merge nibbles |
| X.SHR.M.8 | Crossbar shift right merge bytes |
| X.SHR.M.16 | Crossbar shift right merge doublets |
| X.SHR.M.32 | Crossbar shift right merge quadlets |
| X.SHR.M.64 | Crossbar shift right merge octlets |
| X.SHR.M.128 | Crossbar shift right merge hexlet |

Fig. 43E

Format

X.op.size rd@rc,rb

rd=xopsize(rd,rc,rb)



lsize \leftarrow log(size)

s \leftarrow lsize₂

sz \leftarrow lsize_{1..0}

Fig 43F

Definition

```
def CrossbarInplace(op,size,rd,rc,rb) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  shift ← b and (size-1)
  for i ← 0 to 128-size by size
    case op of
      X.SHR.M:
         $a_{i+size-1..i} \leftarrow c_{i+shift-1..i} \parallel d_{i+size-1..i+shift}$ 
      X.SHL.M:
         $a_{i+size-1..i} \leftarrow d_{i+size-1-shift..i} \parallel c_{i+shift-1..i}$ 
    endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

none

Fig 43G

Operation codes

| | |
|--------------------|---|
| X.COMPRESS.I.2 | Crossbar compress immediate signed pecks |
| X.COMPRESS.I.4 | Crossbar compress immediate signed nibbles |
| X.COMPRESS.I.8 | Crossbar compress immediate signed bytes |
| X.COMPRESS.I.16 | Crossbar compress immediate signed doublets |
| X.COMPRESS.I.32 | Crossbar compress immediate signed quadlets |
| X.COMPRESS.I.64 | Crossbar compress immediate signed octlets |
| X.COMPRESS.I.128 | Crossbar compress immediate signed hexlet |
| X.COMPRESS.I.U.2 | Crossbar compress immediate unsigned pecks |
| X.COMPRESS.I.U.4 | Crossbar compress immediate unsigned nibbles |
| X.COMPRESS.I.U.8 | Crossbar compress immediate unsigned bytes |
| X.COMPRESS.I.U.16 | Crossbar compress immediate unsigned doublets |
| X.COMPRESS.I.U.32 | Crossbar compress immediate unsigned quadlets |
| X.COMPRESS.I.U.64 | Crossbar compress immediate unsigned octlets |
| X.COMPRESS.I.U.128 | Crossbar compress immediate unsigned hexlet |
| X.EXPAND.I.2 | Crossbar expand immediate signed pecks |
| X.EXPAND.I.4 | Crossbar expand immediate signed nibbles |
| X.EXPAND.I.8 | Crossbar expand immediate signed bytes |
| X.EXPAND.I.16 | Crossbar expand immediate signed doublets |
| X.EXPAND.I.32 | Crossbar expand immediate signed quadlets |
| X.EXPAND.I.64 | Crossbar expand immediate signed octlets |
| X.EXPAND.I.128 | Crossbar expand immediate signed hexlet |
| X.EXPAND.I.U.2 | Crossbar expand immediate unsigned pecks |
| X.EXPAND.I.U.4 | Crossbar expand immediate unsigned nibbles |
| X.EXPAND.I.U.8 | Crossbar expand immediate unsigned bytes |
| X.EXPAND.I.U.16 | Crossbar expand immediate unsigned doublets |
| X.EXPAND.I.U.32 | Crossbar expand immediate unsigned quadlets |
| X.EXPAND.I.U.64 | Crossbar expand immediate unsigned octlets |
| X.EXPAND.I.U.128 | Crossbar expand immediate unsigned hexlet |
| X.ROTL.I.2 | Crossbar rotate left immediate pecks |
| X.ROTL.I.4 | Crossbar rotate left immediate nibbles |
| X.ROTL.I.8 | Crossbar rotate left immediate bytes |
| X.ROTL.I.16 | Crossbar rotate left immediate doublets |
| X.ROTL.I.32 | Crossbar rotate left immediate quadlets |
| X.ROTL.I.64 | Crossbar rotate left immediate octlets |
| X.ROTL.I.128 | Crossbar rotate left immediate hexlet |
| X.ROTR.I.2 | Crossbar rotate right immediate pecks |
| X.ROTR.I.4 | Crossbar rotate right immediate nibbles |
| X.ROTR.I.8 | Crossbar rotate right immediate bytes |
| X.ROTR.I.16 | Crossbar rotate right immediate doublets |
| X.ROTR.I.32 | Crossbar rotate right immediate quadlets |
| X.ROTR.I.64 | Crossbar rotate right immediate octlets |
| X.ROTR.I.128 | Crossbar rotate right immediate hexlet |

Fig. 43H

| | |
|-----------------|--|
| X.SHL.I.2 | Crossbar shift left immediate pecks |
| X.SHL.I.2.O | Crossbar shift left immediate signed pecks check overflow |
| X.SHL.I.4 | Crossbar shift left immediate nibbles |
| X.SHL.I.4.O | Crossbar shift left immediate signed nibbles check overflow |
| X.SHL.I.8 | Crossbar shift left immediate bytes |
| X.SHL.I.8.O | Crossbar shift left immediate signed bytes check overflow |
| X.SHL.I.16 | Crossbar shift left immediate doublets |
| X.SHL.I.16.O | Crossbar shift left immediate signed doublets check overflow |
| X.SHL.I.32 | Crossbar shift left immediate quadlets |
| X.SHL.I.32.O | Crossbar shift left immediate signed quadlets check overflow |
| X.SHL.I.64 | Crossbar shift left immediate octlets |
| X.SHL.I.64.O | Crossbar shift left immediate signed octlets check overflow |
| X.SHL.I.128 | Crossbar shift left immediate hexlet |
| X.SHL.I.128.O | Crossbar shift left immediate signed hexlet check overflow |
| X.SHL.I.U.2.O | Crossbar shift left immediate unsigned pecks check overflow |
| X.SHL.I.U.4.O | Crossbar shift left immediate unsigned nibbles check overflow |
| X.SHL.I.U.8.O | Crossbar shift left immediate unsigned bytes check overflow |
| X.SHL.I.U.16.O | Crossbar shift left immediate unsigned doublets check overflow |
| X.SHL.I.U.32.O | Crossbar shift left immediate unsigned quadlets check overflow |
| X.SHL.I.U.64.O | Crossbar shift left immediate unsigned octlets check overflow |
| X.SHL.I.U.128.O | Crossbar shift left immediate unsigned hexlet check overflow |
| X.SHR.I.2 | Crossbar signed shift right immediate pecks |
| X.SHR.I.4 | Crossbar signed shift right immediate nibbles |
| X.SHR.I.8 | Crossbar signed shift right immediate bytes |
| X.SHR.I.16 | Crossbar signed shift right immediate doublets |
| X.SHR.I.32 | Crossbar signed shift right immediate quadlets |
| X.SHR.I.64 | Crossbar signed shift right immediate octlets |
| X.SHR.I.128 | Crossbar signed shift right immediate hexlet |
| X.SHR.I.U.2 | Crossbar shift right immediate unsigned pecks |
| X.SHR.I.U.4 | Crossbar shift right immediate unsigned nibbles |
| X.SHR.I.U.8 | Crossbar shift right immediate unsigned bytes |
| X.SHR.I.U.16 | Crossbar shift right immediate unsigned doublets |
| X.SHR.I.U.32 | Crossbar shift right immediate unsigned quadlets |
| X.SHR.I.U.64 | Crossbar shift right immediate unsigned octlets |
| X.SHR.I.U.128 | Crossbar shift right immediate unsigned hexlet |

Fig. 43H (cont)


Selection

| class | op | size |
|-----------|---|--------------------|
| precision | COMPRESS.I COMPRESS.I.U EXPAND.I EXPAND.I.U | 2 4 8 16 32 64 128 |
| shift | ROTL.I ROTR.I SHL.I SHL.I.O SHL.I.U.O SHR.I SHR.I.U | 2 4 8 16 32 64 128 |
| copy | <i>COPY</i> | |

Format

X.op.size rd=rc,shift

rd=xopsize(rc,shift)



$t \leftarrow 256 - 2 * \text{size} + \text{shift}$

$\text{op}_{1..0} \leftarrow t_{7..6}$

$\text{simm} \leftarrow t_{5..0}$

Fig. 43I

Definition

```

def CrossbarShortImmediate(op,rd,rc,simm)
  case (op1..0 || simm) of
    0..127:
      size ← 128
    128..191:
      size ← 64
    192..223:
      size ← 32
    224..239:
      size ← 16
    240..247:
      size ← 8
    248..251:
      size ← 4
    252..253:
      size ← 2
    254..255:
      raise ReservedInstruction
  endcase
  shift ← (op0 || simm) and (size-1)
  c ← RegRead(rc, 128)
  case (op5..2 || 02) of
    X.COMPRESS.I:
      hsize ← size/2
      for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
          ai+hsize-1..i ← Ci+shift+hsize-1..i+shift
        else
          ai+hsize-1..i ← Cshift-hsizei+size-1 || Ci+size-1..i+shift
        endif
      endfor
      a127..64 ← 0
    X.COMPRESS.I.U:
      hsize ← size/2
      for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
          ai+hsize-1..i ← Ci+shift+hsize-1..i+shift
        else
          ai+hsize-1..i ← 0shift-hsize || Ci+size-1..i+shift
        endif
      endfor
      a127..64 ← 0
  endcase

```

Fig. 43J

```

X.EXPAND.I:
    hsize ← size/2
    for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
             $a_{i+i+size-1..i+i} \leftarrow c_{i+hsize-1}^{hsize-shift} \parallel c_{i+hsize-1..i} \parallel 0^{shift}$ 
        else
             $a_{i+i+size-1..i+i} \leftarrow c_{i+size-shift-1..i} \parallel 0^{shift}$ 
        endif
    endfor
X.EXPAND.I.U:
    hsize ← size/2
    for i ← 0 to 64-hsize by hsize
        if shift ≤ hsize then
             $a_{i+i+size-1..i+i} \leftarrow 0^{hsize-shift} \parallel c_{i+hsize-1..i} \parallel 0^{shift}$ 
        else
             $a_{i+i+size-1..i+i} \leftarrow c_{i+size-shift-1..i} \parallel 0^{shift}$ 
        endif
    endfor
X.SHL.I:
    for i ← 0 to 128-size by size
         $a_{i+size-1..i} \leftarrow c_{i+size-1-shift..i} \parallel 0^{shift}$ 
    endfor
X.SHL.I.O:
    for i ← 0 to 128-size by size
        if  $c_{i+size-1..i+size-1-shift} \neq c_{i+size-1-shift}^{shift+1}$  then
            raise FixedPointArithmetic
        endif
         $a_{i+size-1..i} \leftarrow c_{i+size-1-shift..i} \parallel 0^{shift}$ 
    endfor
X.SHL.I.U.O:
    for i ← 0 to 128-size by size
        if  $c_{i+size-1..i+size-shift} \neq 0^{shift}$  then
            raise FixedPointArithmetic
        endif
         $a_{i+size-1..i} \leftarrow c_{i+size-1-shift..i} \parallel 0^{shift}$ 
    endfor

```

Fig. 43J (cont)

```

X.ROTR.I:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow c_{i+shift-1..i} \parallel c_{i+size-1..i+shift}$ 
  endfor
X.SHR.I:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow c_{i+size-1}^{shift} \parallel c_{i+size-1..i+shift}$ 
  endfor
X.SHR.I.U:
  for i ← 0 to 128-size by size
     $a_{i+size-1..i} \leftarrow 0^{shift} \parallel c_{i+size-1..i+shift}$ 
  endfor
endcase
RegWrite(rd, 128, a)
enddef

```

Exceptions

Fixed-point arithmetic
Reserved Instruction

Fig. 43J (cont)

Operation codes


| | |
|---------------|---|
| X.SHL.M.I.2 | Crossbar shift left merge immediate pecks |
| X.SHL.M.I.4 | Crossbar shift left merge immediate nibbles |
| X.SHL.M.I.8 | Crossbar shift left merge immediate bytes |
| X.SHL.M.I.16 | Crossbar shift left merge immediate doublets |
| X.SHL.M.I.32 | Crossbar shift left merge immediate quadlets |
| X.SHL.M.I.64 | Crossbar shift left merge immediate octlets |
| X.SHL.M.I.128 | Crossbar shift left merge immediate hexlet |
| X.SHR.M.I.2 | Crossbar shift right merge immediate pecks |
| X.SHR.M.I.4 | Crossbar shift right merge immediate nibbles |
| X.SHR.M.I.8 | Crossbar shift right merge immediate bytes |
| X.SHR.M.I.16 | Crossbar shift right merge immediate doublets |
| X.SHR.M.I.32 | Crossbar shift right merge immediate quadlets |
| X.SHR.M.I.64 | Crossbar shift right merge immediate octlets |
| X.SHR.M.I.128 | Crossbar shift right merge immediate hexlet |

Fig 43K

Format

X.op.size rd@rc,shift

rd=xopsize(rc,shift)



$t \leftarrow 256 - 2 * \text{size} + \text{shift}$

$\text{op}_{1..0} \leftarrow t_{7..6}$

$\text{simm} \leftarrow t_{5..0}$

Fig 43L

Definition

```
def CrossbarShortImmediateInplace(op,rd,rc,simm)
  case (op1..0 || simm) of
    0..127:
      size ← 128
    128..191:
      size ← 64
    192..223:
      size ← 32
    224..239:
      size ← 16
    240..247:
      size ← 8
    248..251:
      size ← 4
    252..253:
      size ← 2
    254..255:
      raise ReservedInstruction
  endcase
  shift ← (op0 || simm) and (size-1)
  c ← RegRead(rc, 128)
  d ← RegRead(rd, 128)
  for i ← 0 to 128-size by size
    case (op5..2 || 02) of
      X.SHR.M.I:
        ai+size-1..i ← ci+shift-1..i || di+size-1..i+shift
      X.SHL.M.I:
        ai+size-1..i ← di+size-1-shift..i || ci+shift-1..i
    endcase
  endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Reserved Instruction

Fig 43M

Format

X.EXTRACT ra=rd,rc,rb

ra=xextract(rd,rc,rb)




Fig. 44A

Definition

```
def CrossbarExtract(op,ra,rb,rc,rd) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  case b8..0 of
    0..255:
      gsize ← 128
    256..383:
      gsize ← 64
    384..447:
      gsize ← 32
    448..479:
      gsize ← 16
    480..495:
      gsize ← 8
    496..503:
      gsize ← 4
    504..507:
      gsize ← 2
    508..511:
      gsize ← 1
  endcase
  m ← b12
  as ← signed ← b14
  h ← (2-m)*gsize
  spos ← (b8..0) and ((2-m)*gsize-1)
  dpos ← (0 || b23..16) and (gsize-1)
  sfsz ← (0 || b31..24) and (gsize-1)
  tfsz ← (sfsz = 0) or ((sfsz+dpos) > gsize) ? gsize-dpos : sfsz
  fsz ← (tfsz + spos > h) ? h - spos : tfsz
  for i ← 0 to 128-gsize by gsize
    case op of
      X.EXTRACT:
        if m then
          p ← dgsz+i-1..i
        else
          p ← (d || c)2*(gsize+i)-1..2*i
        endif
      endcase
    v ← (as & ph-1)||p
    w ← (as & vspos+fsz-1)gsize-fsz-dpos || vfsz-1+spos..spos || 0dpos
    if m then
      asz-1+i..i ← cgsz-1+i..dpos+fsz+i || wdpos+fsz-1..dpos || cdpos-1+1..i
    else
      asz-1+i..i ← w
    endif
  endfor
  RegWrite(ra, 128, a)
enddef
```

Exceptions

none

Fig. 44B




Fig. 44C




Fig. 44D

Operation codes

| | |
|--------------|----------------------------|
| E.MUL.X | Ensemble multiply extract |
| E.EXTRACT | Ensemble extract |
| E.SCAL.ADD.X | Ensemble scale add extract |

Fig. 44E

Format

E.op ra=rd,rc,rb

ra=eop(rd,rc,rb)




Fig. 44F

```

def mul(size,h,vs,v,i,ws,w,j) as
    mul ← ((vs&vsize-1+i)h-size || vsize-1+i..i) * ((ws&wsize-1+j)h-size || wsize-1+j..j)
enddef

def EnsembleExtract(op,ra,rb,rc,rd) as
    d ← RegRead(rd, 128)
    c ← RegRead(rc, 128)
    b ← RegRead(rb, 128)
    case b8..0 of
        0..255:
            sgsz ← 128
        256..383:
            sgsz ← 64
        384..447:
            sgsz ← 32
        448..479:
            sgsz ← 16
        480..495:
            sgsz ← 8
        496..503:
            sgsz ← 4
        504..507:
            sgsz ← 2
        508..511:
            sgsz ← 1
    endcase
    l ← b11
    m ← b12
    n ← b13
    signed ← b14
    case op of
        E.EXTRACT:
            gsize ← sgsz
            h ← (2-m)*gsz
            as ← signed
            spos ← (b8..0) and ((2-m)*gsz-1)
        E.SCAL.ADD.X:
            if (sgsz < 8) then
                gsize ← 8
            elseif (sgsz*(n+1) > 32) then
                gsize ← 32/(n+1)
            else
                gsize ← sgsz
            endif
            ds ← cs ← signed
            bs ← signed ^ m
            as ← signed or m or n
            h ← (2*gsz) + 1 + n
            spos ← (b8..0) and (2*gsz-1)
    endcase
enddef

```

Fig. 44G

```

E.MUL.X:
    if (sgsize < 8) then
        gsize ← 8
    elseif (sgsize*(n+1) > 128) then
        gsize ← 128/(n+1)
    else
        gsize ← sgsz
    endif
    ds ← signed
    cs ← signed ^ m
    as ← signed or m or n
    h ← (2*gsz) + n
    spos ← (b8..0) and (2*gsz-1)
endcase
dpos ← (0 || b23..16) and (gsz-1)
r ← spos
sfsz ← (0 || b31..24) and (gsz-1)
tfsz ← (sfsz = 0) or ((sfsz+dpos) > gsz) ? gsz-dpos : sfsz
fsz ← (tfsz + spos > h) ? h - spos : tfsz
if (b10..9 = Z) and not as then
    rnd ← F
else
    rnd ← b10..9
endif
for i ← 0 to 128-gsz by gsz
    case op of
        E.EXTRACT:
            if m then
                p ← dgsz+i-1..i
            else
                p ← (d || c)2*(gsz+i)-1..2*i
            endif
        E.MUL.X:
            if n then
                if (i and gsz) = 0 then
                    p ← mul(gsz,h,ds,d,i,cs,c,i) - mul(gsz,h,ds,d,i+sz,cs,c,i+sz)
                else
                    p ← mul(gsz,h,ds,d,i,cs,c,i+sz) + mul(gsz,h,ds,d,i,cs,c,i+sz)
                endif
            else
                p ← mul(gsz,h,ds,d,i,cs,c,i)
            endif
    endcase
endfor

```

Fig. 44G (cont)

```

E.SCAL.ADD.X:
  if n then
    if (i and gsize) = 0 then
      p ← mul(gsize,h,ds,d,i,bs,b,64+2*gsz)
        + mul(gsize,h,cs,c,i,bs,b,64)
        - mul(gsize,h,ds,d,i+gsz,bs,b,64+3*gsz)
        - mul(gsize,h,cs,c,i+gsz,bs,b,64+gsz)
    else
      p ← mul(gsize,h,ds,d,i,bs,b,64+3*gsz)
        + mul(gsize,h,cs,c,i,bs,b,64+gsz)
        + mul(gsize,h,ds,d,i+gsz,bs,b,64+2*gsz)
        + mul(gsize,h,cs,c,i+gsz,bs,b,64)
    endif
  else
    p ← mul(gsize,h,ds,d,i,bs,b,64+gsz) + mul(gsize,h,cs,c,i,bs,b,64)
  endif
endcase
case rnd of
  N:
    s ← 0h-r || ~pr || prr-1
  Z:
    s ← 0h-r || ph-1r
  F:
    s ← 0h
  C:
    s ← 0h-r || 1r
endcase
v ← ((as & ph-1) || p) + (0 || s)
if (vh..r+fsz = (as & vr+fsz-1)h+1-r-fsz) or not (l and (op = E.EXTRACT)) then
  w ← (as & vr+fsz-1)gsz-fsz-dpos || vfsz-1+r..r || 0dpos
else
  w ← (s ? (vh || ~vhgsz-dpos-1) : 1gsz-dpos) || 0dpos
endif
if m and (op = E.EXTRACT) then
  asize-1+i..i ← cgsz-1+i..dpos+fsz+i || wdpos+fsz-1..dpos || cdpos-1+1..i
else
  asize-1+i..i ← w
endif
endfor
RegWrite(ra, 128, a)
enddef

```

Exceptions

none

Fig. 44G (cont)

| | |
|------------------|-------------------------------------|
| X.DEPOSIT.2 | Crossbar deposit signed pecks |
| X.DEPOSIT.4 | Crossbar deposit signed nibbles |
| X.DEPOSIT.8 | Crossbar deposit signed bytes |
| X.DEPOSIT.16 | Crossbar deposit signed doublets |
| X.DEPOSIT.32 | Crossbar deposit signed quadlets |
| X.DEPOSIT.64 | Crossbar deposit signed octlets |
| X.DEPOSIT.128 | Crossbar deposit signed hexlet |
| X.DEPOSIT.U.2 | Crossbar deposit unsigned pecks |
| X.DEPOSIT.U.4 | Crossbar deposit unsigned nibbles |
| X.DEPOSIT.U.8 | Crossbar deposit unsigned bytes |
| X.DEPOSIT.U.16 | Crossbar deposit unsigned doublets |
| X.DEPOSIT.U.32 | Crossbar deposit unsigned quadlets |
| X.DEPOSIT.U.64 | Crossbar deposit unsigned octlets |
| X.DEPOSIT.U.128 | Crossbar deposit unsigned hexlet |
| X.WITHDRAW.U.2 | Crossbar withdraw unsigned pecks |
| X.WITHDRAW.U.4 | Crossbar withdraw unsigned nibbles |
| X.WITHDRAW.U.8 | Crossbar withdraw unsigned bytes |
| X.WITHDRAW.U.16 | Crossbar withdraw unsigned doublets |
| X.WITHDRAW.U.32 | Crossbar withdraw unsigned quadlets |
| X.WITHDRAW.U.64 | Crossbar withdraw unsigned octlets |
| X.WITHDRAW.U.128 | Crossbar withdraw unsigned hexlet |
| X.WITHDRAW.2 | Crossbar withdraw pecks |
| X.WITHDRAW.4 | Crossbar withdraw nibbles |
| X.WITHDRAW.8 | Crossbar withdraw bytes |
| X.WITHDRAW.16 | Crossbar withdraw doublets |
| X.WITHDRAW.32 | Crossbar withdraw quadlets |
| X.WITHDRAW.64 | Crossbar withdraw octlets |
| X.WITHDRAW.128 | Crossbar withdraw hexlet |

Fig. 45A

Equivalencies

| | |
|--------------------|---|
| <i>X.SEX.I.2</i> | Crossbar extend immediate signed pecks |
| <i>X.SEX.I.4</i> | Crossbar extend immediate signed nibbles |
| <i>X.SEX.I.8</i> | Crossbar extend immediate signed bytes |
| <i>X.SEX.I.16</i> | Crossbar extend immediate signed doublets |
| <i>X.SEX.I.32</i> | Crossbar extend immediate signed quadlets |
| <i>X.SEX.I.64</i> | Crossbar extend immediate signed octlets |
| <i>X.SEX.I.128</i> | Crossbar extend immediate signed hexlet |
| <i>X.ZEX.I.2</i> | Crossbar extend immediate unsigned pecks |
| <i>X.ZEX.I.4</i> | Crossbar extend immediate unsigned nibbles |
| <i>X.ZEX.I.8</i> | Crossbar extend immediate unsigned bytes |
| <i>X.ZEX.I.16</i> | Crossbar extend immediate unsigned doublets |
| <i>X.ZEX.I.32</i> | Crossbar extend immediate unsigned quadlets |
| <i>X.ZEX.I.64</i> | Crossbar extend immediate unsigned octlets |
| <i>X.ZEX.I.128</i> | Crossbar extend immediate unsigned hexlet |

| | | |
|-------------------------------|---|--|
| <i>X.SHL.I.gsize rd=rc,i</i> | → | <i>X.DEPOSIT.gsize rd=rc,size-i,i</i> |
| <i>X.SHR.I.gsize rd=rc,i</i> | → | <i>X.WITHDRAW.gsize rd=rc,size-i,i</i> |
| <i>X.SHRU.I.gsize rd=rc,i</i> | → | <i>X.WITHDRAW.U.gsize rd=rc,size-i,i</i> |
| <i>X.SEX.I.gsize rd=rc,i</i> | → | <i>X.DEPOSIT.gsize rd=rc,i,0</i> |
| <i>X.ZEX.I.gsize rd=rc,i</i> | → | <i>X.DEPOSIT.U.gsize rd=rc,i,0</i> |

Redundancies


| | | |
|--|---|---------------------|
| <i>X.DEPOSIT.gsize rd=rc,gsiz,0</i> | ⇔ | <i>X.COPY rd=rc</i> |
| <i>X.DEPOSIT.U.gsize rd=rc,gsiz,0</i> | ⇔ | <i>X.COPY rd=rc</i> |
| <i>X.WITHDRAW.gsize rd=rc,gsiz,0</i> | ⇔ | <i>X.COPY rd=rc</i> |
| <i>X.WITHDRAW.U.gsize rd=rc,gsiz,0</i> | ⇔ | <i>X.COPY rd=rc</i> |

Fig. 45A (cont'd)

Format

X.op.gsize rd=rc, isize, ishift

rd=xopgszsize(rc, isize, ishift)



assert isize+ishift ≤ gsize

assert isize ≥ 1

ih₀ || gsfs ← 128-gsize+isize-1

ih₁ || gsfp ← 128-gsize+ishift

Fig. 45B

Definition

```
def CrossbarField(op,rd,rc,gsfp,gsfs) as
  c ← RegRead(rc, 128)
  case ((op1 || gsfp) and (op0 || gsfs)) of
    0..63:
      gsize ← 128
    64..95:
      gsize ← 64
    96..111:
      gsize ← 32
    112..119:
      gsize ← 16
    120..123:
      gsize ← 8
    124..125:
      gsize ← 4
    126:
      gsize ← 2
    127:
      raise ReservedInstruction
  endcase
  ishift ← (op1 || gsfp) and (gsize-1)
  isize ← ((op0 || gsfs) and (gsize-1))+1
  if (ishift+isize>gsize)
    raise ReservedInstruction
  endif
  case op of
    X.DEPOSIT:
      for i ← 0 to 128-gsize by gsize
        ai+gsize-1..i ← cgsize- isize- ishift .. i+ isize- 1 || Ci+ isize- 1..i || 0ishift
      endfor
    X.DEPOSIT.U:
      for i ← 0 to 128-gsize by gsize
        ai+gsize-1..i ← 0gsize- isize- ishift .. i+ isize- 1 || Ci+ isize- 1..i || 0ishift
      endfor
    X.WITHDRAW:
      for i ← 0 to 128-gsize by gsize
        ai+gsize-1..i ← csize- isize .. i+ isize+ ishift- 1 || Ci+ isize+ ishift- 1..i+ ishift
      endfor
    X.WITHDRAW.U:
      for i ← 0 to 128-gsize by gsize
        ai+gsize-1..i ← 0size- isize .. i+ isize+ ishift- 1 || Ci+ isize+ ishift- 1..i+ ishift
      endfor
  endcase
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Reserved instruction

Fig. 45C




Fig. 45D




Fig. 45E




Fig. 45F

Operation codes


| | |
|-----------------|---------------------------------|
| X.DEPOSIT.M.2 | Crossbar deposit merge pecks |
| X.DEPOSIT.M.4 | Crossbar deposit merge nibbles |
| X.DEPOSIT.M.8 | Crossbar deposit merge bytes |
| X.DEPOSIT.M.16 | Crossbar deposit merge doublets |
| X.DEPOSIT.M.32 | Crossbar deposit merge quadlets |
| X.DEPOSIT.M.64 | Crossbar deposit merge octlets |
| X.DEPOSIT.M.128 | Crossbar deposit merge hexlet |

Fig 45G

Format

X.op.gsize rd@rc, isize, ishift

rd=xopgszsize(rd,rc,isize,ishift)



assert isize+ishift ≤ gsize

assert isize ≥ 1

ih₀ || gsfs ← 128-gsize+isize-1

ih₁ || gsfp ← 128-gsize+ishift

Fig 45H

Definition

```
def CrossbarFieldInplace(op,rd,rc,gsfp,gsfs) as
  c ← RegRead(rc, 128)
  d ← RegRead(rd, 128)
  case ((op1 || gsfp) and (op0 || gsfs)) of
    0..63:
      gsize ← 128
    64..95:
      gsize ← 64
    96..111:
      gsize ← 32
    112..119:
      gsize ← 16
    120..123:
      gsize ← 8
    124..125:
      gsize ← 4
    126:
      gsize ← 2
    127:
      raise ReservedInstruction
  endcase
  ishift ← (op1 || gsfp) and (gsize-1)
  isize ← ((op0 || gsfs) and (gsize-1))+1
  if (ishift+isize>gsize)
    raise ReservedInstruction
  endif
  for i ← 0 to 128-gsize by gsize
    aj+gsize-1..i ← dj+gsize-1..i+isize+ishift || ci+isize-1..i || di+ishift-1..i
  endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Reserved instruction

Fig 45I




Fig 45J

| | |
|---------------|----------------------------------|
| X.SHUFFLE.4 | Crossbar shuffle within pecks |
| X.SHUFFLE.8 | Crossbar shuffle within bytes |
| X.SHUFFLE.16 | Crossbar shuffle within doublets |
| X.SHUFFLE.32 | Crossbar shuffle within quadlets |
| X.SHUFFLE.64 | Crossbar shuffle within octlets |
| X.SHUFFLE.128 | Crossbar shuffle within hexlet |
| X.SHUFFLE.256 | Crossbar shuffle within trilet |

Fig. 46A


Format

X.SHUFFLE.256 rd=rc,rb,v,w,h

X.SHUFFLE.size rd=rcb,v,w

rd=xshuffle256(rc,rb,v,w,h)

rd=xshufflesize(rcb,v,w)



rc ← rb ← rcb

x ← log₂(size)

y ← log₂(v)

z ← log₂(w)

op ← ((x*x*x-3*x*x-4*x)/6-(z*z-z)/2+x*z+y) + (size=256)*(h*32-56)

Fig. 46B

Definition

```
def CrossbarShuffle(major,rd,rc,rb,op)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  if rc=rb then
    case op of
      0..55:
        for x ← 2 to 7; for y ← 0 to x-2; for z ← 1 to x-y-1
          if op = ((x*x*x-3*x*x-4*x)/6-(z*z-z)/2+x*z+y) then
            for i ← 0 to 127
              ai ← c(i6..x || iy+z-1..y || ix-1..y+z || iy-1..0)
            end
          endif
        endfor; endfor; endfor
      56..63:
        raise ReservedInstruction
    endcase
  elseif
    case op4..0 of
      0..27:
        cb ← c || b
        x ← 8
        h ← op5
        for y ← 0 to x-2; for z ← 1 to x-y-1
          if op4..0 = ((17*z-z*z)/2-8+y) then
            for i ← h*128 to 127+h*128
              ai-h*128 ← cb(iy+z-1..y || ix-1..y+z || iy-1..0)
            end
          endif
        endfor; endfor
      28..31:
        raise ReservedInstruction
    endcase
  endif
  RegWrite(rd, 128, a)
enddef
```

Exceptions

Reserved Instruction

Fig. 46C




Fig. 46D





Fig. 46E

Format

X.SWIZZLE rd=rc,icopy,iswap

rd=xswizzle(rc,icopy,iswap)



icopya \leftarrow icopy_{5..0}

iswapa \leftarrow iswap_{5..0}

ih \leftarrow icopy₆ || iswap₆

Fig. 47A

Definition

```
def GroupSwizzleImmediate(ih,rd,rc,icopya,iswapa) as
  icopy  $\leftarrow$  ih1 || icopya
  iswap  $\leftarrow$  ih0 || iswapa
  c  $\leftarrow$  RegRead(rc, 128)
  for i  $\leftarrow$  0 to 127
    ai  $\leftarrow$  c(i & icopy) ^ iswap
  endfor
  RegWrite(rd, 128, a)
enddef
```

Exceptions

none

Fig. 47B




Fig. 47C

| | |
|------------|-----------------------|
| X.SELECT.8 | Crossbar select bytes |
|------------|-----------------------|

Format

op ra=rd,rc,rb

ra=op(rd,rc,rb)




Fig. 47D

Definition

```

def CrossbarTernary(op,rd,rc,rb,ra) as
  d ← RegRead(rd, 128)
  c ← RegRead(rc, 128)
  b ← RegRead(rb, 128)
  dc ← d || c
  for i ← 0 to 15
    j ← b8*i+4..8*i
    a8*i+7..8*i ← dc8*j+7..8*j
  endfor
  RegWrite(ra, 128, a)
enddef

```

Exceptions

none

Fig. 47E

Pin summary

| | | |
|------------|----|---|
| A20M# | I | Address bit 20 Mask is an emulator signal. |
| A31..A3 | IO | Address , in combination with byte enable , indicate the physical addresses of memory or device that is the target of a bus transaction. This signal is an output, when the processor is initiating the bus transaction, and an input when the processor is receiving an inquire transaction or snooping another processor's bus transaction. |
| ADS# | IO | Address Strobe , when asserted, indicates new bus transaction by the processor, with valid address and byte enable simultaneously driven. |
| ADSC# | O | Address Strobe Copy is driven identically to address strobe |
| AHOLD | I | Address HOLD , when asserted, causes the processor to cease driving address and address parity in the next bus clock cycle. |
| AP | IO | Address Parity contains even parity on the same cycle as address . Address parity is generated by the processor when address is an output, and is checked when address is an input. A parity error causes a bus error machine check. |
| APCHK# | O | Address Parity CHeck is asserted two bus clocks after EADS# if address parity is not even parity of address . |
| APICEN | I | Advanced Programmable Interrupt Controller ENable is not implemented. |
| BE7#..BE0# | IO | Byte Enable indicates which bytes are the subject of a read or write transaction and are driven on the same cycle as address . |
| BF1..BF0 | I | Bus Frequency is sampled to permit software to select the ratio of the processor clock to the bus clock. |
| BOFF# | I | BackOFF is sampled on the rising edge of each bus clock, and when asserted, the processor floats bus signals on the next bus clock and aborts the current bus cycle, until the backoff signal is sampled negated. |
| BP3..BP0 | O | BreakPoint is an emulator signal. |
| BRDY# | I | Bus ReaDY indicates that valid data is present on data on a read transaction, or that data has been accepted on a write transaction. |
| BRDYC# | I | Bus ReaDY Copy is identical to BRDY#; asserting either signal has the same effect. |
| BREQ | O | Bus REQuest indicates a processor initiated bus request. |

Fig. 48

| | | |
|----------|----|---|
| BUSCHK# | I | BUS CHeck is sampled on the rising edge of the bus clock, and when asserted, causes a bus error machine check. |
| CACHE# | O | CACHE , when asserted, indicates a cacheable read transaction or a burst write transaction. |
| CLK | I | bus CLock provides the bus clock timing edge and the frequency reference for the processor clock. |
| CPUTYP | I | CPU TYPE , if low indicates the primary processor, if high, the dual processor. |
| D/C# | I | Data/Code is driven with the address signal to indicate data, code, or special cycles. |
| D63..D0 | IO | Data communicates 64 bits of data per bus clock . |
| D/P# | O | Dual/Primary is driven (asserted, low) with address on the primary processor |
| DP7..DP0 | IO | Data Parity contains even parity on the same cycle as data . A parity error causes a bus error machine check. |
| DPEN# | IO | Dual Processing Enable is asserted (driven low) by a Dual processor at reset and sampled by a Primary processor at the falling edge of reset. |
| EADS# | I | External Address Strobe indicates that an external device has driven address for an inquire cycle. |
| EWBE# | I | External Write Buffer Empty indicates that the external system has no pending write. |
| FERR# | O | Floating point ERROR is an emulator signal. |
| FLUSH# | I | cache FLUSH is an emulator signal. |
| FRCMC# | I | Functional Redundancy Checking Master/Checker is not implemented. |
| HIT# | IO | HIT indicates that an inquire cycle or cache snoop hits a valid line. |
| HITM# | IO | HIT to a Modified line indicates that an inquire cycle or cache snoop hits a sub-block in the M cache state. |
| HLDA | O | bus HoLD Acknowledge is asserted (driven high) to acknowledge a bus hold request |
| HOLD | I | bus HOLD request causes the processor to float most of its pins and assert bus hold acknowledge after completing all outstanding bus transactions, or during reset. |
| IERR# | O | Internal ERROR is an emulator signal. |
| IGNNE# | I | IGNore Numeric Error is an emulator signal. |
| INIT | I | INITialization is an emulator signal. |
| INTR | I | maskable INteRrupt is an emulator signal. |
| INV | I | INValidation controls whether to invalidate the addressed cache sub-block on an inquire transaction. |

Fig. 48 (cont'd)

| | | |
|--------------|----|---|
| KEN# | I | Cache ENable is driven with address to indicate that the read or write transaction is cacheable. |
| LINT1..LINT0 | I | Local INTerrupt is not implemented. |
| LOCK# | O | bus LOCK is driven starting with address and ending after bus ready to indicate a locked series of bus transactions. |
| M/IO# | O | Memory/Input Output is driven with address to indicate a memory or I/O transaction. |
| NA# | I | Next Address indicates that the external system will accept an address for a new bus cycle in two bus clocks. |
| NMI | I | Non Maskable Interrupt is an emulator signal. |
| PBGNT# | IO | Private Bus GraNT is driven between Primary and Dual processors to indicate that bus arbitration has completed, granting a new master access to the bus. |
| PBREQ# | IO | Private Bus REQuest is driven between Primary and Dual processors to request a new master access to the bus. |
| PCD | O | Page Cache Disable is driven with address to indicate a not cacheable transaction. |
| PCHK# | O | Parity CHeck is asserted (driven low) two bus clocks after data appears with odd parity on enabled bytes. |
| PHIT# | IO | Private HIT is driven between Primary and Dual processors to indicate that the current read or write transaction addresses a valid cache sub-block in the slave processor. |
| PHITM# | IO | Private HIT Modified is driven between Primary and Dual processors to indicate that the current read or write transaction addresses a modified cache sub-block in the slave processor. |
| PICCLK | I | Programmable Interrupt Controller CLock is not implemented. |
| PICD1..PICD0 | IO | Programmable Interrupt Controller Data is not implemented. |
| PEN# | I | Parity Enable , if active on the data cycle, allows a parity error to cause a bus error machine check. |
| PM1..PM0 | O | Performance Monitoring is an emulator signal. |
| PRDY | O | Probe ReaDY is not implemented. |
| PWT | O | Page Write Through is driven with address to indicate a not write allocate transaction. |
| R/S# | I | Run/Stop is not implemented. |
| RESET | I | RESET causes a processor reset. |
| SCYC | O | Split CYCle is asserted during bus lock to indicate that more than two transactions are in the series of bus transactions. |

Fig. 48 (cont'd)

| | | |
|----------------------|---|--|
| SMI# | I | S ystem M anagement I nterrupt is an emulator signal. |
| SMI ACT # | O | S ystem M anagement I nterrupt ACT ive is an emulator signal. |
| STPCLK# | I | SToP CLoCK is an emulator signal. |
| TCK | I | Test CLoCK follows IEEE 1149.1. |
| TDI | I | Test Data Input follows IEEE 1149.1. |
| TDO | O | Test Data Output follows IEEE 1149.1. |
| TMS | I | Test Mode Select follows IEEE 1149.1. |
| TRST# | I | Test ReSeT follows IEEE 1149.1. |
| VCC2 | I | VCC of 2.8V at 25 pins |
| VCC3 | I | VCC of 3.3V at 28 pins |
| VCC2DET# | O | VCC2 DETect sets appropriate VCC2 voltage level. |
| VSS | I | VSS supplied at 53 pins |
| W/R# | O | Write/Read is driven with address to indicate write vs. read transaction. |
| WB/WT# | I | Write Back/Write Through is returned to indicate that data is permitted to be cached as write back. |

Fig. 48 (cont'd)

Electrical Specifications

| Clock rate | 66 MHz | | 75 MHz | | 100 MHz | | 133 MHz | | |
|--|--------|------|--------|------|---------|------|---------|-----|------|
| Parameter | min | max | min | max | min | max | min | max | unit |
| CLK frequency | 33.3 | 66.7 | 37.5 | 75 | 50 | 100 | | 133 | MHz |
| CLK period | 15.0 | 30.0 | 13.3 | 26.3 | 10.0 | 20.0 | | | ns |
| CLK high time ($\geq 2V$) | 4.0 | | 4.0 | | 3.0 | | | | ns |
| CLK low time ($\leq 0.8V$) | 4.0 | | 4.0 | | 3.0 | | | | ns |
| CLK rise time (0.8V- \rightarrow 2V) | 0.15 | 1.5 | 0.15 | 1.5 | 0.15 | 1.5 | | | ns |
| CLK fall time (2V- \rightarrow 0.8V) | 0.15 | 1.5 | 0.15 | 1.5 | 0.15 | 1.5 | | | ns |
| CLK period stability | | 250 | | 250 | | 250 | | | ps |

Fig. 49A

| | | | | | | | | | |
|-------------------------------|-----|------|-----|-----|-----|-----|--|--|----|
| A31..3 valid delay | 1.1 | 6.3 | 1.1 | 4.5 | 1.1 | 4.0 | | | ns |
| A31..3 float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| ADS# valid delay | 1.0 | 6.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| ADS# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| ADSC# valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| ADSC# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| AP valid delay | 1.0 | 8.5 | 1.0 | 5.5 | 1.0 | 5.5 | | | ns |
| AP float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| APCHK# valid delay | 1.0 | 8.3 | 1.0 | 4.5 | 1.0 | 4.5 | | | ns |
| BE7..0# valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| BE7..0# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| BP3..0 valid delay | 1.0 | 10.0 | | | | | | | ns |
| BREQ valid delay | 1.0 | 8.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| CACHE# valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| CACHE# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| D/C# valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| D/C# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| D63..0 write data valid delay | 1.3 | 7.5 | 1.3 | 4.5 | 1.3 | 4.5 | | | ns |
| D63..0 write data float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| DP7..0 write data valid delay | 1.3 | 7.5 | 1.3 | 4.5 | 1.3 | 4.5 | | | ns |
| DP7..0 write data float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| FERR# valid delay | 1.0 | 8.3 | 1.0 | 4.5 | 1.0 | 4.5 | | | ns |
| HIT# valid delay | 1.0 | 6.8 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| HITM# valid delay | 1.1 | 6.0 | 1.1 | 4.5 | 1.1 | 4.0 | | | ns |
| HLDA valid delay | 1.0 | 6.8 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| IERR# valid delay | 1.0 | 8.3 | | | | | | | ns |
| LOCK# valid delay | 1.1 | 7.0 | 1.1 | 4.5 | 1.1 | 4.0 | | | ns |
| LOCK# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| M/IO# valid delay | 1.0 | 5.9 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| M/IO# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| PCD valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| PCD float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| PCHK# valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.5 | | | ns |
| PM1..0 valid delay | 1.0 | 10.0 | | | | | | | ns |
| PRDY valid delay | 1.0 | 8.0 | | | | | | | ns |
| PWT valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| PWT float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| SCYC valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| SCYC float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |
| SMIACK# valid delay | 1.0 | 7.3 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| W/R# valid delay | 1.0 | 7.0 | 1.0 | 4.5 | 1.0 | 4.0 | | | ns |
| W/R# float delay | | 10.0 | | 7.0 | | 7.0 | | | ns |

Fig. 49B

| | | | | | | | | | |
|-----------------------------|-----|--|-----|--|-----|--|--|--|-----|
| A31..5 setup time | 6.0 | | 3.0 | | 3.0 | | | | ns |
| A31..5 hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| A20M# setup time | 5.0 | | 3.0 | | 3.0 | | | | ns |
| A20M# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| AHOLD setup time | 5.5 | | 3.5 | | 3.5 | | | | ns |
| AHOLD hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| AP setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| AP hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| BOFF# setup time | 5.5 | | 3.5 | | 3.5 | | | | ns |
| BOFF# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| BRDY# setup time | 5.0 | | 3.0 | | 3.0 | | | | ns |
| BRDY# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| BRDYC# setup time | 5.0 | | 3.0 | | 3.0 | | | | ns |
| BRDYC# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| BUSCHK# setup time | 5.0 | | 3.0 | | 3.0 | | | | ns |
| BUSCHK# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| D63..0 read data setup time | 2.8 | | 1.7 | | 1.7 | | | | ns |
| D63..0 read data hold time | 1.5 | | 1.5 | | 1.5 | | | | ns |
| DP7..0 read data setup time | 2.8 | | 1.7 | | 1.7 | | | | ns |
| DP7..0 read data hold time | 1.5 | | 1.5 | | 1.5 | | | | ns |
| EADS# setup time | 5.0 | | 3.0 | | 3.0 | | | | ns |
| EADS# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| EWBE# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| EWBE# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| FLUSH# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| FLUSH# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| FLUSH# async pulse width | 2 | | 2 | | 2 | | | | CLK |
| HOLD setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| HOLD hold time | 1.5 | | 1.5 | | 1.5 | | | | ns |
| IGNNE# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| IGNNE# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| IGNNE# async pulse width | 2 | | 2 | | 2 | | | | CLK |
| INIT setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| INIT hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| INIT async pulse width | 2 | | 2 | | 2 | | | | CLK |
| INTR setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| INTR hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| INV setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| INV hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| KEN# setup time | 5.0 | | 3.0 | | 3.0 | | | | ns |
| KEN# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| NA# setup time | 4.5 | | 1.7 | | 1.7 | | | | ns |

Fig. 49C

| | | | | | | | | | |
|------------------------|-----|--|-----|--|-----|--|--|--|-----|
| NA# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| NMI setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| NMI hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| NMI async pulse width | 2 | | 2 | | 2 | | | | CLK |
| PEN# setup time | 4.8 | | 1.7 | | 1.7 | | | | ns |
| PEN# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| R/S# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| R/S# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| R/S# async pulse width | 2 | | 2 | | 2 | | | | CLK |
| SMI# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| SMI# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| SMI# async pulse width | 2 | | 2 | | 2 | | | | CLK |
| STPCLK# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| STPCLK# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| WB/WT# setup time | 4.5 | | 1.7 | | 1.7 | | | | ns |
| WB/WT# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |

Fig. 49C (cont'd)

| | | | | | | | | | |
|-------------------|-----|--|-----|--|-----|--|--|--|-----|
| RESET setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| RESET hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| RESET pulse width | 15 | | 15 | | 15 | | | | CLK |
| RESET active | 1.0 | | 1.0 | | 1.0 | | | | ms |
| BF2..0 setup time | 1.0 | | 1.0 | | 1.0 | | | | ms |
| BF2..0 hold time | 2 | | 2 | | 2 | | | | CLK |
| BRDYC# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| BRDYC# setup time | 2 | | 2 | | 2 | | | | CLK |
| BRDYC# hold time | 2 | | 2 | | 2 | | | | CLK |
| FLUSH# setup time | 5.0 | | 1.7 | | 1.7 | | | | ns |
| FLUSH# hold time | 1.0 | | 1.0 | | 1.0 | | | | ns |
| FLUSH# setup time | 2 | | 2 | | 2 | | | | CLK |
| FLUSH# hold time | 2 | | 2 | | 2 | | | | CLK |

Fig. 49D

| | | | | | | | | | |
|-----------------------------------|-----|------|--|--|--|--|--|--|-----|
| <u>PBREQ# flight time</u> | 0 | 2.0 | | | | | | | ns |
| <u>PBGNT# flight time</u> | 0 | 2.0 | | | | | | | ns |
| <u>PHIT# flight time</u> | 0 | 2.0 | | | | | | | ns |
| <u>PHITM# flight time</u> | 0 | 1.8 | | | | | | | ns |
| <u>A31..5 setup time</u> | 3.7 | | | | | | | | ns |
| <u>A31..5 hold time</u> | 0.8 | | | | | | | | ns |
| <u>D/C# setup time</u> | 4.0 | | | | | | | | ns |
| <u>D/C# hold time</u> | 0.8 | | | | | | | | ns |
| <u>W/R# setup time</u> | 4.0 | | | | | | | | ns |
| <u>W/R# hold time</u> | 0.8 | | | | | | | | ns |
| <u>CACHE# setup time</u> | 4.0 | | | | | | | | ns |
| <u>CACHE# hold time</u> | 1.0 | | | | | | | | ns |
| <u>LOCK# setup time</u> | 4.0 | | | | | | | | ns |
| <u>LOCK# hold time</u> | 0.8 | | | | | | | | ns |
| <u>SCYC setup time</u> | 4.0 | | | | | | | | ns |
| <u>SCYC hold time</u> | 0.8 | | | | | | | | ns |
| <u>ADS# setup time</u> | 5.8 | | | | | | | | ns |
| <u>ADS# hold time</u> | 0.8 | | | | | | | | ns |
| <u>M/IO# setup time</u> | 5.8 | | | | | | | | ns |
| <u>M/IO# hold time</u> | 0.8 | | | | | | | | ns |
| <u>HIT# setup time</u> | 6.0 | | | | | | | | ns |
| <u>HIT# hold time</u> | 1.0 | | | | | | | | ns |
| <u>HITM# setup time</u> | 6.0 | | | | | | | | ns |
| <u>HITM# hold time</u> | 0.7 | | | | | | | | ns |
| <u>HLDA setup time</u> | 6.0 | | | | | | | | ns |
| <u>HLDA hold time</u> | 0.8 | | | | | | | | ns |
| <u>DPEN# valid time</u> | | 10.0 | | | | | | | CLK |
| <u>DPEN# hold time</u> | 2.0 | | | | | | | | CLK |
| <u>D/P# valid delay (primary)</u> | 1.0 | 8.0 | | | | | | | ns |

Fig. 49E

| | | | | | | | | | |
|--|------|-----|--|--|------|-----|--|--|---------|
| TCK frequency | | 25 | | | | 25 | | | MH z |
| TCK period | 40.0 | | | | 40.0 | | | | ns |
| TCK high time ($\geq 2V$) | 14.0 | | | | 14.0 | | | | ns |
| TCK low time ($\leq 0.8V$) | 14.0 | | | | 14.0 | | | | ns |
| TCK rise time (0.8V- \rightarrow 2V) | | 5.0 | | | | 5.0 | | | ns |
| TCK fall time (2V- \rightarrow 0.8V) | | 5.0 | | | | 5.0 | | | ns |
| TRST# pulse width | 30.0 | | | | 30.0 | | | | ns |

Fig. 49F

| | | | | | | | | | |
|-------------------------|-----|------|--|--|-----|------|--|--|----|
| TDI setup time | 5.0 | | | | 5.0 | | | | ns |
| TDI hold time | 9.0 | | | | 9.0 | | | | ns |
| TMS setup time | 5.0 | | | | 5.0 | | | | ns |
| TMS hold time | 9.0 | | | | 9.0 | | | | ns |
| TDO valid delay | 3.0 | 13.0 | | | 3.0 | 13.0 | | | ns |
| TDO float delay | | 16.0 | | | | 16.0 | | | ns |
| all outputs valid delay | 3.0 | 13.0 | | | 3.0 | 13.0 | | | ns |
| all outputs float delay | | 16.0 | | | | 16.0 | | | ns |
| all inputs setup time | 5.0 | | | | 5.0 | | | | ns |
| all inputs hold time | 9.0 | | | | 9.0 | | | | ns |

Fig. 49G

Operation codes

| | |
|------------|---|
| L.8 | Load signed byte |
| L.16.B | Load signed doublet big-endian |
| L.16.A.B | Load signed doublet aligned big-endian |
| L.16.L | Load signed doublet little-endian |
| L.16.A.L | Load signed doublet aligned little-endian |
| L.32.B | Load signed quadlet big-endian |
| L.32.A.B | Load signed quadlet aligned big-endian |
| L.32.L | Load signed quadlet little-endian |
| L.32.A.L | Load signed quadlet aligned little-endian |
| L.64.B | Load signed octlet big-endian |
| L.64.A.B | Load signed octlet aligned big-endian |
| L.64.L | Load signed octlet little-endian |
| L.64.A.L | Load signed octlet aligned little-endian |
| L.128.B | Load hexlet big-endian |
| L.128.A.B | Load hexlet aligned big-endian |
| L.128.L | Load hexlet little-endian |
| L.128.A.L | Load hexlet aligned little-endian |
| L.U.8 | Load unsigned byte |
| L.U.16.B | Load unsigned doublet big-endian |
| L.U.16.A.B | Load unsigned doublet aligned big-endian |
| L.U.16.L | Load unsigned doublet little-endian |
| L.U.16.A.L | Load unsigned doublet aligned little-endian |
| L.U.32.B | Load unsigned quadlet big-endian |
| L.U.32.A.B | Load unsigned quadlet aligned big-endian |
| L.U.32.L | Load unsigned quadlet little-endian |
| L.U.32.A.L | Load unsigned quadlet aligned little-endian |
| L.U.64.B | Load unsigned octlet big-endian |
| L.U.64.A.B | Load unsigned octlet aligned big-endian |
| L.U.64.L | Load unsigned octlet little-endian |
| L.U.64.A.L | Load unsigned octlet aligned little-endian |

Fig. 50A

Selection

| number format | type | size | alignment | ordering |
|--------------------------|------|----------|-----------|----------|
| signed byte | | 8 | | |
| unsigned byte | U | 8 | | |
| signed integer | | 16 32 64 | | L B |
| signed integer aligned | | 16 32 64 | A | L B |
| unsigned integer | U | 16 32 64 | | L B |
| unsigned integer aligned | U | 16 32 64 | A | L B |
| register | | 128 | | L B |
| register aligned | | 128 | A | L B |

Format

op rd=rc,rb

rd=op(rc,rb)




Fig. 50B

Definition

```
def Load(op,rd,rc,rb) as
  case op of
    L16L, L32L, L8, L16AL, L32AL, L16B, L32B, L16AB, L32AB,
    L64L, L64AL, L64B, L64AB:
      signed ← true
    LU16L, LU32L, LU8, LU16AL, LU32AL, LU16B, LU32B, LU16AB, LU32AB,
    LU64L, LU64AL, LU64B, LU64AB:
      signed ← false
    L128L, L128AL, L128B, L128AB:
      signed ← undefined
  endcase
  case op of
    L8, LU8:
      size ← 8
    L16L, LU16L, L16AL, LU16AL, L16B, LU16B, L16AB, LU16AB:
      size ← 16
    L32L, LU32L, L32AL, LU32AL, L32B, LU32B, L32AB, LU32AB:
      size ← 32
    L64L, LU64L, L64AL, LU64AL, L64B, LU64B, L64AB, LU64AB:
      size ← 64
    L128L, L128AL, L128B, L128AB:
      size ← 128
  endcase
  lsize ← log(size)
  case op of
    L16L, LU16L, L32L, LU32L, L64L, LU64L, L128L,
    L16AL, LU16AL, L32AL, LU32AL, L64AL, LU64AL, L128AL:
      order ← L
    L16B, LU16B, L32B, LU32B, L64B, LU64B, L128B,
    L16AB, LU16AB, L32AB, LU32AB, L64AB, LU64AB, L128AB:
      order ← B
    L8, LU8:
      order ← undefined
  endcase
```

Fig. 50C

```

c ← RegRead(rc, 64)
b ← RegRead(rb, 64)
VirtAddr ← c + (b66-lsize..0 || 0lsize-3)
case op of
  L16AL, LU16AL, L32AL, LU32AL, L64AL, LU64AL, L128AL,
  L16AB, LU16AB, L32AB, LU32AB, L64AB, LU64AB, L128AB:
    if (csize-4..0 ≠ 0 then
      raise AccessDisallowedByVirtualAddress
    endif
  L16L, LU16L, L32L, LU32L, L64L, LU64L, L128L,
  L16B, LU16B, L32B, LU32B, L64B, LU64B, L128B:
  L8, LU8:
endcase
m ← LoadMemory(c,VirtAddr,size,order)
a ← (msize-1 and signed)128-size || m
RegWrite(rd, 128, a)
enddef

```

Exceptions

Access disallowed by virtual address
 Access disallowed by tag
 Access disallowed by global TB
 Access disallowed by local TB
 Access detail required by tag
 Access detail required by local TB
 Access detail required by global TB
 Local TB miss
 Global TB miss

Fig. 50C (cont)

Operation codes

| | |
|--------------|---|
| L.I.8 | Load immediate signed byte |
| L.I.16.A.B | Load immediate signed doublet aligned big-endian |
| L.I.16.B | Load immediate signed doublet big-endian |
| L.I.16.A.L | Load immediate signed doublet aligned little-endian |
| L.I.16.L | Load immediate signed doublet little-endian |
| L.I.32.A.B | Load immediate signed quadlet aligned big-endian |
| L.I.32.B | Load immediate signed quadlet big-endian |
| L.I.32.A.L | Load immediate signed quadlet aligned little-endian |
| L.I.32.L | Load immediate signed quadlet little-endian |
| L.I.64.A.B | Load immediate signed octlet aligned big-endian |
| L.I.64.B | Load immediate signed octlet big-endian |
| L.I.64.A.L | Load immediate signed octlet aligned little-endian |
| L.I.64.L | Load immediate signed octlet little-endian |
| L.I.128.A.B | Load immediate hexlet aligned big-endian |
| L.I.128.B | Load immediate hexlet big-endian |
| L.I.128.A.L | Load immediate hexlet aligned little-endian |
| L.I.128.L | Load immediate hexlet little-endian |
| L.I.U.8 | Load immediate unsigned byte |
| L.I.U.16.A.B | Load immediate unsigned doublet aligned big-endian |
| L.I.U.16.B | Load immediate unsigned doublet big-endian |
| L.I.U.16.A.L | Load immediate unsigned doublet aligned little-endian |
| L.I.U.16.L | Load immediate unsigned doublet little-endian |
| L.I.U.32.A.B | Load immediate unsigned quadlet aligned big-endian |
| L.I.U.32.B | Load immediate unsigned quadlet big-endian |
| L.I.U.32.A.L | Load immediate unsigned quadlet aligned little-endian |
| L.I.U.32.L | Load immediate unsigned quadlet little-endian |
| L.I.U.64.A.B | Load immediate unsigned octlet aligned big-endian |
| L.I.U.64.B | Load immediate unsigned octlet big-endian |
| L.I.U.64.A.L | Load immediate unsigned octlet aligned little-endian |
| L.I.U.64.L | Load immediate unsigned octlet little-endian |

Fig. 51A

Selection

| number format | type | size | alignment | ordering |
|--------------------------|------|----------|-----------|----------|
| signed byte | | 8 | | |
| unsigned byte | U | 8 | | |
| signed integer | | 16 32 64 | | L B |
| signed integer aligned | | 16 32 64 | A | L B |
| unsigned integer | U | 16 32 64 | | L B |
| unsigned integer aligned | U | 16 32 64 | A | L B |
| register | | 128 | | L B |
| register aligned | | 128 | A | L B |

Format

op rd=rc,offset

rd=op(rc,offset)




Fig. 51B

Definition

```

def LoadImmediate(op,rd,rc,offset) as
  case op of
    LI16L, LI32L, LI8, LI16AL, LI32AL, LI16B, LI32B, LI16AB, LI32AB:
      LI64L, LI64AL, LI64B, LI64AB:
        signed ← true
    LIU16L, LIU32L, LIU8, LIU16AL, LIU32AL, .
    LIU16B, LIU32B, LIU16AB, LIU32AB:
    LIU64L, LIU64AL, LIU64B, LIU64AB:
      signed ← false
    LI128L, LI128AL, LI128B, LI128AB:
      signed ← undefined
  endcase
  case op of
    LI8, LIU8:
      size ← 8
    LI16L, LIU16L, LI16AL, LIU16AL, LI16B, LIU16B, LI16AB, LIU16AB:
      size ← 16
    LI32L, LIU32L, LI32AL, LIU32AL, LI32B, LIU32B, LI32AB, LIU32AB:
      size ← 32
    LI64L, LIU64L, LI64AL, LIU64AL, LI64B, LIU64B, LI64AB, LIU64AB:
      size ← 64
    LI128L, LI128AL, LI128B, LI128AB:
      size ← 128
  endcase
  lsize ← log(size)
  case op of
    LI16L, LIU16L, LI32L, LIU32L, LI64L, LIU64L, LI128L,
    LI16AL, LIU16AL, LI32AL, LIU32AL, LI64AL, LIU64AL, LI128AL:
      order ← LI
    LI16B, LIU16B, LI32B, LIU32B, LI64B, LIU64B, LI128B,
    LI16AB, LIU16AB, LI32AB, LIU32AB, LI64AB, LIU64AB, LI128AB:
      order ← B
    LI8, LIU8:
      order ← undefined
  endcase

```

Fig. 51C

```

c ← RegRead(rc, 64)
VirtAddr ← c + (offset55-size || offset || 0size-3)
case op of
  LI16AL, LIU16AL, LI32AL, LIU32AL, LI64AL, LIU64AL, LI128AL,
  LI16AB, LIU16AB, LI32AB, LIU32AB, LI64AB, LIU64AB, LI128AB:
    if (csize-4..0 ≠ 0 then
      raise AccessDisallowedByVirtualAddress
    endif
  LI16L, LIU16L, LI32L, LIU32L, LI64L, LIU64L, LI128L,
  LI16B, LIU16B, LI32B, LIU32B, LI64B, LIU64B, LI128B:
  LI8, LIU8:
endcase
m ← LoadMemory(c, VirtAddr, size, order)
a ← (msize-1 and signed)128-size || m
RegWrite(rd, 128, a)
enddef

```

Exceptions

Access disallowed by virtual address
 Access disallowed by tag
 Access disallowed by global TB
 Access disallowed by local TB
 Access detail required by tag
 Access detail required by local TB
 Access detail required by global TB
 Local TB miss
 Global TB miss

Fig. 51C (cont)

Operation codes

| | |
|--------------|--|
| S.8 | Store byte |
| S.16.B | Store double big-endian |
| S.16.A.B | Store double aligned big-endian |
| S.16.L | Store double little-endian |
| S.16.A.L | Store double aligned little-endian |
| S.32.B | Store quadlet big-endian |
| S.32.A.B | Store quadlet aligned big-endian |
| S.32.L | Store quadlet little-endian |
| S.32.A.L | Store quadlet aligned little-endian |
| S.64.B | Store octlet big-endian |
| S.64.A.B | Store octlet aligned big-endian |
| S.64.L | Store octlet little-endian |
| S.64.A.L | Store octlet aligned little-endian |
| S.128.B | Store hexlet big-endian |
| S.128.A.B | Store hexlet aligned big-endian |
| S.128.L | Store hexlet little-endian |
| S.128.A.L | Store hexlet aligned little-endian |
| S.MUX.64.A.B | Store multiplex octlet aligned big-endian |
| S.MUX.64.A.L | Store multiplex octlet aligned little-endian |

Fig. 52A

S lection

| number format | op | size | alignment | ordering |
|-----------------|-----|--------------|-----------|----------|
| byte | | 8 | | |
| integer | | 16 32 64 128 | | L B |
| integer aligned | | 16 32 64 128 | A | L B |
| multiplex | MUX | 64 | A | L B |

Format

op rd,rc,rb

op(rd,rc,rb)




Fig. 52B

Definition

```
def Store(op,rd,rc,rb) as
  case op of
    S8:
      size ← 8
    S16L, S16AL, S16B, S16AB:
      size ← 16
    S32L, S32AL, S32B, S32AB:
      size ← 32
    S64L, S64AL, S64B, S64AB,
    SMUX64AB, SMUX64AL:
      size ← 64
    S128L, S128AL, S128B, S128AB:
      size ← 128
  endcase
  lsize ← log(size)
  case op of
    S8:
      order ← undefined
    S16L, S32L, S64L, S128L,
    S16AL, S32AL, S64AL, S128AL, SMUX64AL:
      order ← L
    S16B, S32B, S64B, S128B,
    S16AB, S32AB, S64AB, S128AB, SMUX64AB:
      order ← B
  endcase
  c ← RegRead(rc, 64)
  b ← RegRead(rb, 64)
  VirtAddr ← c + (b66-lsize..0 || 0lsize-3)
  case op of
    S16AL, S32AL, S64AL, S128AL,
    S16AB, S32AB, S64AB, S128AB,
    SMUX64AB, SMUX64AL:
      if (clsize-4..0 ≠ 0 then
        raise AccessDisallowedByVirtualAddress
      endif
    S16L, S32L, S64L, S128L,
    S16B, S32B, S64B, S128B:
    S8:
  endcase
```

Fig. 52C

```

d ← RegRead(rd, 128)
case op of
  S8,
  S16L, S16AL, S16B, S16AB,
  S32L, S32AL, S32B, S32AB,
  S64L, S64AL, S64B, S64AB,
  S128L, S128AL, S128B, S128AB:
    StoreMemory(c,VirtAddr,size,order,dsize-1..0)
  SMUX64AB, SMUX64AL:
    lock
      a ← LoadMemoryW(c,VirtAddr,size,order)
      m ← (d127..64 & d63..0) | (a & ~d63..0)
      StoreMemory(c,VirtAddr,size,order,m)
    endlock
endcase
enddef

```

Exceptions

Access disallowed by virtual address
 Access disallowed by tag
 Access disallowed by global TB
 Access disallowed by local TB
 Access detail required by tag
 Access detail required by local TB
 Access detail required by global TB
 Local TB miss
 Global TB miss

Fig. 52C (cont)

Operation codes

| | |
|---------------|--|
| S.I.8 | Store immediate byte |
| S.I.16.A.B | Store immediate double aligned big-endian |
| S.I.16.B | Store immediate double big-endian |
| S.I.16.A.L | Store immediate double aligned little-endian |
| S.I.16.L | Store immediate double little-endian |
| S.I.32.A.B | Store immediate quadlet aligned big-endian |
| S.I.32.B | Store immediate quadlet big-endian |
| S.I.32.A.L | Store immediate quadlet aligned little-endian |
| S.I.32.L | Store immediate quadlet little-endian |
| S.I.64.A.B | Store immediate octlet aligned big-endian |
| S.I.64.B | Store immediate octlet big-endian |
| S.I.64.A.L | Store immediate octlet aligned little-endian |
| S.I.64.L | Store immediate octlet little-endian |
| S.I.128.A.B | Store immediate hexlet aligned big-endian |
| S.I.128.B | Store immediate hexlet big-endian |
| S.I.128.A.L | Store immediate hexlet aligned little-endian |
| S.I.128.L | Store immediate hexlet little-endian |
| S.MUXI.64.A.B | Store multiplex immediate octlet aligned big-endian |
| S.MUXI.64.A.L | Store multiplex immediate octlet aligned little-endian |

Fig. 53A

Selection

| number format | op | size | alignment | ordering |
|-----------------|-----|--------------|-----------|----------|
| byte | | 8 | | |
| integer | | 16 32 64 128 | | L B |
| integer aligned | | 16 32 64 128 | A | L B |
| multiplex | MUX | 64 | A | L B |

Format

S.op.l.size.align.order rd,rc,offset

sopisizealignorder(rd,rc,offset)




Fig. 53B

Definition

```

def StoreImmediate(op,rd,rc,offset) as
  case op of
    SI8:
      size ← 8
    SI16L, SI16AL, SI16B, SI16AB:
      size ← 16
    SI32L, SI32AL, SI32B, SI32AB:
      size ← 32
    SI64L, SI64AL, SI64B, SI64AB, SMUXI64AB, SMUXI64AL:
      size ← 64
    SI128L, SI128AL, SI128B, SI128AB:
      size ← 128
  endcase
  lsize ← log(size)
  case op of
    SI8:
      order ← undefined
    SI16L, SI32L, SI64L, SI128L,
    SI16AL, SI32AL, SI64AL, SI128AL, SMUXI64AL:
      order ← L
    SI16B, SI32B, SI64B, SI128B,
    SI16AB, SI32AB, SI64AB, SI128AB, SMUXI64AB:
      order ← B
  endcase
  c ← RegRead(rc, 64)
  VirtAddr ← c + (offset << 55-lsize || offset || 0<sup>lsize-3</sup>)
  case op of
    SI16AL, SI32AL, SI64AL, SI128AL,
    SI16AB, SI32AB, SI64AB, SI128AB,
    SMUXI64AB, SMUXI64AL:
      if (c<sub>size-4..0</sub> ≠ 0 then
        raise AccessDisallowedByVirtualAddress
      endif
    SI16L, SI32L, SI64L, SI128L,
    SI16B, SI32B, SI64B, SI128B:
    SI8:
  endcase
endcase

```

Fig. 53C

```

d ← RegRead(rd, 128)
case op of
  SI8,
  SI16L, SI16AL, SI16B, SI16AB,
  SI32L, SI32AL, SI32B, SI32AB,
  SI64L, SI64AL, SI64B, SI64AB,
  SI128L, SI128AL, SI128B, SI128AB:
    StoreMemory(c,VirtAddr,size,order,dsize-1..0)
  SMUXI64AB, SMUXI64AL:
    lock
      a ← LoadMemoryW(c,VirtAddr,size,order)
      m ← (d127..64 & d63..0) | (a & ~d63..0)
      StoreMemory(c,VirtAddr,size,order,m)
    endlock
endcase
enddef

```

Exceptions

Access disallowed by virtual address
 Access disallowed by tag
 Access disallowed by global TB
 Access disallowed by local TB
 Access detail required by tag
 Access detail required by local TB
 Access detail required by global TB
 Local TB miss
 Global TB miss

Fig. 53C (cont)